

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2019

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	13	7,685	5,032	84	401	96	9	39	243	182	2	3	70	0
	Flex	.00	.00	.00	.35	.10	.44	.45	.36	.59	.42	.70	.31	.60	0.00
	Rigid	.00	.00	.00	.40	.10	.67	.94	.43	.99	.92	.72	.32	1.12	0.00
	GVW	1.0	4.0	6.5	22.9	15.4	31.1	51.9	28.4	50.2	66.5	42.7	44.2	66.2	0.0
E	Num	6	3,828	2,613	43	246	32	5	20	117	85	1	2	30	0
	Flex	.00	.00	.00	.46	.09	.62	.45	.50	.73	.51	1.93	.68	.88	0.00
	Rigid	.00	.00	.00	.53	.10	.95	1.02	.59	1.26	1.06	2.03	.73	1.63	0.00
	GVW	1.1	4.2	6.7	24.8	15.2	34.1	54.1	31.3	55.8	63.3	55.1	59.3	79.9	0.0
W	Num	7	3,857	2,419	41	155	64	3	19	126	97	1	3	40	0
	Flex	.00	.00	.00	.24	.12	.35	.50	.21	.45	.33	.19	.13	.42	0.00
	Rigid	.00	.00	.00	.27	.12	.53	.98	.23	.74	.81	.18	.13	.80	0.00
	GVW	1.0	3.8	6.2	20.8	15.7	29.7	49.9	25.4	44.9	69.9	38.1	36.6	57.7	0.0
E Lane1	Num	6	3,828	2,613	43	246	32	5	20	117	85	1	2	30	0
	Flex	.00	.00	.00	.46	.09	.62	.45	.50	.73	.51	1.93	.68	.88	0.00
	Rigid	.00	.00	.00	.53	.10	.95	1.02	.59	1.26	1.06	2.03	.73	1.63	0.00
	GVW	1.1	4.2	6.7	24.8	15.2	34.1	54.1	31.3	55.8	63.3	55.1	59.3	79.9	0.0
W Lane1	Num	7	3,857	2,419	41	155	64	3	19	126	97	1	3	40	0
	Flex	.00	.00	.00	.24	.12	.35	.50	.21	.45	.33	.19	.13	.42	0.00
	Rigid	.00	.00	.00	.27	.12	.53	.98	.23	.74	.81	.18	.13	.80	0.00
	GVW	1.0	3.8	6.2	20.8	15.7	29.7	49.9	25.4	44.9	69.9	38.1	36.6	57.7	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2019

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9