

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	10	6,381	4,438	94	387	96	9	36	233	186	2	4	70	0
	Flex	.00	.00	.00	.32	.09	.46	.54	.35	.55	.44	.41	.49	.56	0.00
	Rigid	.00	.00	.00	.35	.09	.69	1.14	.41	.92	.98	.39	.53	1.01	0.00
	GVW	1.0	4.0	6.6	21.7	15.3	31.4	55.1	28.1	49.6	68.3	41.9	49.0	66.3	0.0
E	Num	5	3,152	2,213	45	245	34	5	18	117	90	1	2	31	0
	Flex	.00	.00	.00	.44	.09	.69	.64	.49	.69	.56	.72	.83	.77	0.00
	Rigid	.00	.00	.00	.50	.09	1.01	1.34	.58	1.15	1.15	.68	.88	1.41	0.00
	GVW	1.0	4.2	6.9	24.2	15.1	35.1	58.4	30.8	54.0	64.3	49.4	62.8	77.1	0.0
W	Num	5	3,228	2,225	49	142	62	5	18	116	96	1	3	39	0
	Flex	.00	.00	.00	.20	.11	.34	.32	.18	.41	.33	.18	.27	.42	0.00
	Rigid	.00	.00	.00	.22	.11	.52	.71	.20	.69	.82	.17	.29	.76	0.00
	GVW	1.0	3.7	6.2	19.4	15.7	29.5	48.2	24.5	45.1	72.3	36.8	38.9	59.8	0.0
E Lane1	Num	5	3,152	2,213	45	245	34	5	18	117	90	1	2	31	0
	Flex	.00	.00	.00	.44	.09	.69	.64	.49	.69	.56	.72	.83	.77	0.00
	Rigid	.00	.00	.00	.50	.09	1.01	1.34	.58	1.15	1.15	.68	.88	1.41	0.00
	GVW	1.0	4.2	6.9	24.2	15.1	35.1	58.4	30.8	54.0	64.3	49.4	62.8	77.1	0.0
W Lane1	Num	5	3,228	2,225	49	142	62	5	18	116	96	1	3	39	0
	Flex	.00	.00	.00	.20	.11	.34	.32	.18	.41	.33	.18	.27	.42	0.00
	Rigid	.00	.00	.00	.22	.11	.52	.71	.20	.69	.82	.17	.29	.76	0.00
	GVW	1.0	3.7	6.2	19.4	15.7	29.5	48.2	24.5	45.1	72.3	36.8	38.9	59.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9