

Idaho Transportation Department

Monthly WIM Distribution for Dec-2019

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	5,273	3,694	77	242	54	7	35	166	131	2	4	39	0
	Flex	.00	.00	.00	.22	.08	.41	.26	.29	.49	.36	.66	.29	.44	0.00
	Rigid	.00	.00	.00	.23	.08	.56	.75	.32	.79	.76	.64	.30	.77	0.00
	GVW	1.8	4.0	6.4	19.5	14.1	30.6	48.6	28.6	48.5	64.6	45.5	44.0	60.2	0.0
E	Num	1	2,632	1,851	37	161	21	5	18	82	60	1	2	15	0
	Flex	.00	.00	.00	.30	.07	.59	.28	.42	.62	.43	.84	.61	.65	0.00
	Rigid	.00	.00	.00	.32	.07	.78	.83	.46	.99	.78	.81	.63	1.16	0.00
	GVW	1.8	4.2	6.7	21.5	13.8	33.5	49.8	32.3	52.6	56.4	51.4	57.8	70.5	0.0
W	Num	1	2,640	1,842	41	81	33	3	17	84	71	2	2	24	0
	Flex	.00	.00	.00	.14	.10	.31	.25	.17	.36	.29	.50	.10	.32	0.00
	Rigid	.00	.00	.00	.14	.10	.44	.52	.18	.58	.72	.49	.10	.56	0.00
	GVW	1.9	3.8	6.1	17.6	14.9	29.1	42.7	25.0	44.3	71.7	40.6	35.1	55.0	0.0
E Lane1	Num	1	2,632	1,851	37	161	21	5	18	82	60	1	2	15	0
	Flex	.00	.00	.00	.30	.07	.59	.28	.42	.62	.43	.84	.61	.65	0.00
	Rigid	.00	.00	.00	.32	.07	.78	.83	.46	.99	.78	.81	.63	1.16	0.00
	GVW	1.8	4.2	6.7	21.5	13.8	33.5	49.8	32.3	52.6	56.4	51.4	57.8	70.5	0.0
W Lane1	Num	1	2,640	1,842	41	81	33	3	17	84	71	2	2	24	0
	Flex	.00	.00	.00	.14	.10	.31	.25	.17	.36	.29	.50	.10	.32	0.00
	Rigid	.00	.00	.00	.14	.10	.44	.52	.18	.58	.72	.49	.10	.56	0.00
	GVW	1.9	3.8	6.1	17.6	14.9	29.1	42.7	25.0	44.3	71.7	40.6	35.1	55.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2019

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9