

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	4,638	3,537	79	252	44	4	27	164	140	1	3	38	0
	Flex	.00	.00	.00	.27	.10	.52	.25	.35	.53	.46	.38	.28	.54	0.00
	Rigid	.00	.00	.00	.31	.11	.75	.54	.41	.89	.99	.35	.30	.94	0.00
	GVW	2.3	4.1	6.4	21.0	14.2	32.6	40.4	28.4	50.0	69.2	41.7	41.4	63.4	0.0
E	Num	2	2,273	1,759	39	166	16	2	12	76	58	0	1	12	0
	Flex	.00	.00	.00	.39	.11	.74	.69	.53	.69	.64	0.00	.67	.88	0.00
	Rigid	.00	.00	.00	.45	.11	1.10	1.24	.63	1.19	1.27	0.00	.73	1.58	0.00
	GVW	2.2	4.3	6.6	23.3	13.9	36.0	54.5	31.6	54.8	62.4	0.0	56.7	77.0	0.0
W	Num	1	2,365	1,778	40	85	28	3	15	89	82	1	2	27	0
	Flex	.00	.00	.00	.15	.10	.39	.14	.18	.38	.34	.38	.13	.39	0.00
	Rigid	.00	.00	.00	.15	.10	.54	.36	.21	.62	.82	.35	.14	.66	0.00
	GVW	2.1	3.8	6.2	18.5	14.6	30.7	37.7	25.9	45.8	74.6	41.7	35.8	57.1	0.0
E Lane1	Num	2	2,273	1,759	39	166	16	2	12	76	58	0	1	12	0
	Flex	.00	.00	.00	.39	.11	.74	.69	.53	.69	.64	0.00	.67	.88	0.00
	Rigid	.00	.00	.00	.45	.11	1.10	1.24	.63	1.19	1.27	0.00	.73	1.58	0.00
	GVW	2.2	4.3	6.6	23.3	13.9	36.0	54.5	31.6	54.8	62.4	0.0	56.7	77.0	0.0
W Lane1	Num	1	2,365	1,778	40	85	28	3	15	89	82	1	2	27	0
	Flex	.00	.00	.00	.15	.10	.39	.14	.18	.38	.34	.38	.13	.39	0.00
	Rigid	.00	.00	.00	.15	.10	.54	.36	.21	.62	.82	.35	.14	.66	0.00
	GVW	2.1	3.8	6.2	18.5	14.6	30.7	37.7	25.9	45.8	74.6	41.7	35.8	57.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9