

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	5,344	3,787	85	323	59	9	28	177	141	1	2	39	0
	Flex	.00	.00	.00	.30	.11	.48	.20	.46	.64	.48	.39	.49	.64	0.00
	Rigid	.00	.00	.00	.34	.11	.72	.56	.54	1.09	1.05	.36	.58	1.18	0.00
	GVW	.9	4.1	6.5	21.4	14.0	32.1	45.6	30.5	52.1	71.1	42.9	45.3	66.7	0.0
E	Num	1	2,623	1,883	44	224	22	5	13	79	57	1	1	12	0
	Flex	.00	.00	.00	.43	.11	.80	.22	.79	.91	.74	.61	1.31	1.32	0.00
	Rigid	.00	.00	.00	.50	.11	1.27	.57	.96	1.58	1.48	.57	1.52	2.43	0.00
	GVW	.9	4.4	6.7	23.7	13.7	38.3	45.7	36.9	59.0	67.3	47.9	65.4	86.4	0.0
W	Num	3	2,721	1,904	41	99	37	6	15	98	85	1	2	27	0
	Flex	.00	.00	.00	.16	.10	.30	.15	.17	.42	.30	.36	.11	.37	0.00
	Rigid	.00	.00	.00	.17	.10	.42	.46	.18	.69	.76	.34	.11	.69	0.00
	GVW	.9	3.9	6.2	18.9	14.6	28.6	44.2	25.1	46.4	74.4	42.2	34.5	58.9	0.0
E Lane1	Num	1	2,623	1,883	44	224	22	5	13	79	57	1	1	12	0
	Flex	.00	.00	.00	.43	.11	.80	.22	.79	.91	.74	.61	1.31	1.32	0.00
	Rigid	.00	.00	.00	.50	.11	1.27	.57	.96	1.58	1.48	.57	1.52	2.43	0.00
	GVW	.9	4.4	6.7	23.7	13.7	38.3	45.7	36.9	59.0	67.3	47.9	65.4	86.4	0.0
W Lane1	Num	3	2,721	1,904	41	99	37	6	15	98	85	1	2	27	0
	Flex	.00	.00	.00	.16	.10	.30	.15	.17	.42	.30	.36	.11	.37	0.00
	Rigid	.00	.00	.00	.17	.10	.42	.46	.18	.69	.76	.34	.11	.69	0.00
	GVW	.9	3.9	6.2	18.9	14.6	28.6	44.2	25.1	46.4	74.4	42.2	34.5	58.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9