

# Idaho Transportation Department

## Monthly WIM Distribution for May-2020

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	8	5,154	4,134	82	394	96	12	37	189	177	2	4	64	0
	Flex	.00	.00	.00	.33	.11	.44	.43	.36	.59	.39	.53	.53	.58	0.00
	Rigid	.00	.00	.00	.39	.11	.67	.89	.41	.98	.85	.50	.56	1.04	0.00
	GVW	1.0	4.0	6.6	23.3	15.2	30.8	48.4	28.0	49.9	65.4	46.7	49.4	64.4	0.0
E	Num	5	2,536	2,057	43	264	29	8	19	90	77	1	2	27	0
	Flex	.00	.00	.00	.43	.09	.72	.52	.56	.82	.51	.68	1.07	.99	0.00
	Rigid	.00	.00	.00	.52	.10	1.11	1.11	.65	1.37	.99	.64	1.13	1.76	0.00
	GVW	1.1	4.2	7.0	25.7	14.9	36.2	54.8	32.3	57.1	59.9	50.1	67.1	83.0	0.0
W	Num	4	2,617	2,078	40	130	67	5	18	98	99	1	3	37	0
	Flex	.00	.00	.00	.21	.13	.30	.36	.14	.40	.30	.41	.12	.33	0.00
	Rigid	.00	.00	.00	.24	.13	.45	.74	.14	.65	.74	.38	.12	.61	0.00
	GVW	1.0	3.8	6.3	20.5	15.9	28.2	45.6	23.1	43.7	69.6	44.1	34.8	53.8	0.0
E Lane1	Num	5	2,536	2,057	43	264	29	8	19	90	77	1	2	27	0
	Flex	.00	.00	.00	.43	.09	.72	.52	.56	.82	.51	.68	1.07	.99	0.00
	Rigid	.00	.00	.00	.52	.10	1.11	1.11	.65	1.37	.99	.64	1.13	1.76	0.00
	GVW	1.1	4.2	7.0	25.7	14.9	36.2	54.8	32.3	57.1	59.9	50.1	67.1	83.0	0.0
W Lane1	Num	4	2,617	2,078	40	130	67	5	18	98	99	1	3	37	0
	Flex	.00	.00	.00	.21	.13	.30	.36	.14	.40	.30	.41	.12	.33	0.00
	Rigid	.00	.00	.00	.24	.13	.45	.74	.14	.65	.74	.38	.12	.61	0.00
	GVW	1.0	3.8	6.3	20.5	15.9	28.2	45.6	23.1	43.7	69.6	44.1	34.8	53.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for May-2020

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9