

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6,651	7,128	5,074	80	466	111	15	40	229	166	3	4	67	0
	Flex	.01	.00	.00	.33	.09	.40	.52	.33	.55	.40	.70	.52	.54	0.00
	Rigid	.02	.00	.00	.39	.09	.61	.91	.37	.92	.86	.67	.54	.96	0.00
	GVW	4.1	4.0	6.6	22.9	15.2	30.8	48.8	27.2	48.9	64.5	49.4	49.7	60.7	0.0
E	Num	3,355	3,508	2,557	39	307	38	11	23	112	80	2	2	29	0
	Flex	.02	.00	.00	.43	.08	.57	.47	.45	.72	.48	.97	.96	.83	0.00
	Rigid	.03	.00	.00	.52	.08	.84	.96	.53	1.21	.98	.93	1.00	1.48	0.00
	GVW	4.3	4.3	7.0	25.4	14.9	34.3	52.1	29.8	55.2	61.1	55.6	65.1	76.5	0.0
W	Num	3,397	3,620	2,517	40	158	73	5	17	117	85	2	3	38	0
	Flex	.01	.00	.00	.22	.12	.33	.46	.17	.38	.31	.48	.14	.35	0.00
	Rigid	.02	.00	.00	.25	.12	.51	.71	.19	.63	.73	.47	.14	.63	0.00
	GVW	4.1	3.7	6.3	20.3	15.6	29.3	44.2	24.2	42.6	67.3	44.3	36.3	52.4	0.0
E Lane1	Num	3,355	3,508	2,557	39	307	38	11	23	112	80	2	2	29	0
	Flex	.02	.00	.00	.43	.08	.57	.47	.45	.72	.48	.97	.96	.83	0.00
	Rigid	.03	.00	.00	.52	.08	.84	.96	.53	1.21	.98	.93	1.00	1.48	0.00
	GVW	4.3	4.3	7.0	25.4	14.9	34.3	52.1	29.8	55.2	61.1	55.6	65.1	76.5	0.0
W Lane1	Num	3,397	3,620	2,517	40	158	73	5	17	117	85	2	3	38	0
	Flex	.01	.00	.00	.22	.12	.33	.46	.17	.38	.31	.48	.14	.35	0.00
	Rigid	.02	.00	.00	.25	.12	.51	.71	.19	.63	.73	.47	.14	.63	0.00
	GVW	4.1	3.7	6.3	20.3	15.6	29.3	44.2	24.2	42.6	67.3	44.3	36.3	52.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9