

Idaho Transportation Department

Monthly WIM Distribution for Feb-2024

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	7,329	3,486	8	209	88	19	68	199	150	2	5	32	0
	Flex	.05	.00	.01	.75	.33	.51	.46	.37	.90	.62	2.55	.98	.90	0.00
	Rigid	.10	.00	.01	.94	.33	.85	1.01	.42	1.69	1.64	2.53	1.27	1.95	0.00
	GVW	9.5	3.8	5.6	30.1	19.0	36.3	56.7	29.4	62.7	81.2	69.5	69.1	88.0	0.0
E	Num	4	3,206	1,891	3	94	43	13	28	106	79	1	2	15	0
	Flex	.02	.00	.00	.71	.37	.57	.47	.39	.90	.52	1.94	1.25	1.12	0.00
	Rigid	.05	.00	.00	.93	.36	.92	1.04	.45	1.69	1.25	1.90	1.54	2.45	0.00
	GVW	10.5	2.7	4.5	31.3	20.0	37.5	56.8	30.0	63.6	71.9	65.5	74.9	99.5	0.0
W	Num	5	4,122	1,595	6	115	45	9	40	94	71	1	3	16	0
	Flex	.05	.00	.01	.80	.31	.47	.53	.35	.88	.71	3.15	.61	.72	0.00
	Rigid	.10	.00	.01	.96	.30	.79	1.04	.40	1.68	2.01	3.16	.87	1.55	0.00
	GVW	7.5	4.7	7.0	28.6	18.2	35.5	59.3	29.1	61.7	90.9	73.8	61.7	78.8	0.0
E Lane1	Num	4	3,206	1,891	3	94	43	13	28	106	79	1	2	15	0
	Flex	.02	.00	.00	.71	.37	.57	.47	.39	.90	.52	1.94	1.25	1.12	0.00
	Rigid	.05	.00	.00	.93	.36	.92	1.04	.45	1.69	1.25	1.90	1.54	2.45	0.00
	GVW	10.5	2.7	4.5	31.3	20.0	37.5	56.8	30.0	63.6	71.9	65.5	74.9	99.5	0.0
W Lane1	Num	5	4,122	1,595	6	115	45	9	40	94	71	1	3	16	0
	Flex	.05	.00	.01	.80	.31	.47	.53	.35	.88	.71	3.15	.61	.72	0.00
	Rigid	.10	.00	.01	.96	.30	.79	1.04	.40	1.68	2.01	3.16	.87	1.55	0.00
	GVW	7.5	4.7	7.0	28.6	18.2	35.5	59.3	29.1	61.7	90.9	73.8	61.7	78.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2024

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9