

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	23	7,428	3,672	8	221	94	19	89	216	162	1	4	39	0
	Flex	.03	.00	.01	.65	.34	.52	.40	.35	.93	.62	.42	.92	.95	0.00
	Rigid	.06	.00	.01	.79	.33	.85	.81	.41	1.74	1.65	.39	1.14	1.98	0.00
	GVW	6.7	3.8	5.7	26.1	18.8	35.7	50.1	28.1	62.7	81.2	37.2	67.4	87.2	0.0
E	Num	11	3,298	2,008	3	99	48	13	37	112	84	0	2	19	0
	Flex	.01	.00	.00	.75	.37	.55	.39	.35	.93	.49	0.00	1.10	1.14	0.00
	Rigid	.03	.00	.00	.92	.36	.89	.82	.41	1.74	1.17	0.00	1.35	2.37	0.00
	GVW	7.2	2.7	4.6	27.0	19.6	36.3	47.2	28.5	63.6	68.5	0.0	68.7	96.4	0.0
W	Num	13	4,130	1,664	5	122	45	6	51	104	78	1	2	20	0
	Flex	.08	.00	.01	.59	.31	.49	.36	.34	.91	.74	.42	.67	.78	0.00
	Rigid	.17	.00	.01	.70	.31	.82	.75	.41	1.73	2.14	.39	.85	1.66	0.00
	GVW	7.1	4.7	7.0	26.1	18.1	35.3	50.1	27.8	61.8	95.2	37.2	63.1	79.1	0.0
E Lane1	Num	11	3,298	2,008	3	99	48	13	37	112	84	0	2	19	0
	Flex	.01	.00	.00	.75	.37	.55	.39	.35	.93	.49	0.00	1.10	1.14	0.00
	Rigid	.03	.00	.00	.92	.36	.89	.82	.41	1.74	1.17	0.00	1.35	2.37	0.00
	GVW	7.2	2.7	4.6	27.0	19.6	36.3	47.2	28.5	63.6	68.5	0.0	68.7	96.4	0.0
W Lane1	Num	13	4,130	1,664	5	122	45	6	51	104	78	1	2	20	0
	Flex	.08	.00	.01	.59	.31	.49	.36	.34	.91	.74	.42	.67	.78	0.00
	Rigid	.17	.00	.01	.70	.31	.82	.75	.41	1.73	2.14	.39	.85	1.66	0.00
	GVW	7.1	4.7	7.0	26.1	18.1	35.3	50.1	27.8	61.8	95.2	37.2	63.1	79.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9