

Idaho Transportation Department

Monthly WIM Distribution for Mar-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	2,818	1,786	1	55	32	3	29	220	184	1	4	59	0
	Flex	.00	.00	.00	.51	.48	.36	.33	.21	.64	.41	.04	.47	.59	0.00
	Rigid	.00	.00	.00	.61	.62	.53	.45	.24	1.11	.89	.07	.59	1.10	0.00
	GVW	2.3	4.4	3.9	26.0	26.0	30.6	32.6	26.9	52.8	64.3	23.2	52.4	73.6	0.0
N	Num	3	1,400	896	1	24	16	2	18	115	99	1	2	17	0
	Flex	.00	.00	.00	.38	.30	.40	.29	.24	.60	.38	.02	.64	.78	0.00
	Rigid	.00	.00	.00	.41	.30	.62	.40	.26	1.05	.75	.04	.76	1.41	0.00
	GVW	2.3	4.2	4.0	24.1	18.5	31.9	30.7	27.4	53.2	55.4	22.9	58.5	74.4	0.0
S	Num	2	1,418	890	1	31	16	2	11	106	85	1	3	42	0
	Flex	.00	.00	.00	1.42	.61	.32	.36	.17	.67	.42	.06	.35	.54	0.00
	Rigid	.00	.00	.00	1.74	.85	.44	.48	.21	1.15	1.04	.11	.45	1.05	0.00
	GVW	2.6	4.6	3.8	29.4	31.2	29.4	35.8	25.8	52.4	74.5	26.4	47.9	75.2	0.0
N Lane1	Num	3	1,400	896	1	24	16	2	18	115	99	1	2	17	0
	Flex	.00	.00	.00	.38	.30	.40	.29	.24	.60	.38	.02	.64	.78	0.00
	Rigid	.00	.00	.00	.41	.30	.62	.40	.26	1.05	.75	.04	.76	1.41	0.00
	GVW	2.3	4.2	4.0	24.1	18.5	31.9	30.7	27.4	53.2	55.4	22.9	58.5	74.4	0.0
S Lane1	Num	2	1,418	890	1	31	16	2	11	106	85	1	3	42	0
	Flex	.00	.00	.00	1.42	.61	.32	.36	.17	.67	.42	.06	.35	.54	0.00
	Rigid	.00	.00	.00	1.74	.85	.44	.48	.21	1.15	1.04	.11	.45	1.05	0.00
	GVW	2.6	4.6	3.8	29.4	31.2	29.4	35.8	25.8	52.4	74.5	26.4	47.9	75.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9