

Idaho Transportation Department

Monthly WIM Distribution for Apr-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	3,110	1,945	2	60	28	5	36	225	161	1	3	71	0
	Flex	.00	.00	.00	.53	.60	.42	.69	.31	.68	.46	.18	.84	.65	0.00
	Rigid	.00	.00	.00	.67	.80	.67	.93	.34	1.18	1.00	.25	.98	1.24	0.00
	GVW	2.4	4.3	4.1	28.6	27.1	30.4	32.8	25.0	51.8	61.6	29.8	54.1	71.9	0.0
N	Num	2	1,553	979	2	27	13	3	23	122	92	1	2	18	0
	Flex	.00	.00	.00	.51	.32	.54	.58	.29	.61	.42	.28	.88	.68	0.00
	Rigid	.00	.00	.00	.64	.32	.91	.79	.30	1.06	.83	.48	1.03	1.07	0.00
	GVW	2.2	4.1	4.1	30.1	18.4	33.2	30.8	25.6	52.5	55.1	36.9	57.4	65.8	0.0
S	Num	2	1,556	966	2	32	15	3	13	103	68	1	2	53	0
	Flex	.00	.00	.00	.65	.83	.32	1.10	.31	.77	.49	.12	.71	.64	0.00
	Rigid	.00	.00	.00	.85	1.20	.47	1.46	.36	1.33	1.19	.13	.83	1.30	0.00
	GVW	2.7	4.5	4.1	31.5	33.8	28.0	34.5	24.0	51.0	69.9	26.8	49.9	74.6	0.0
N Lane1	Num	2	1,553	979	2	27	13	3	23	122	92	1	2	18	0
	Flex	.00	.00	.00	.51	.32	.54	.58	.29	.61	.42	.28	.88	.68	0.00
	Rigid	.00	.00	.00	.64	.32	.91	.79	.30	1.06	.83	.48	1.03	1.07	0.00
	GVW	2.2	4.1	4.1	30.1	18.4	33.2	30.8	25.6	52.5	55.1	36.9	57.4	65.8	0.0
S Lane1	Num	2	1,556	966	2	32	15	3	13	103	68	1	2	53	0
	Flex	.00	.00	.00	.65	.83	.32	1.10	.31	.77	.49	.12	.71	.64	0.00
	Rigid	.00	.00	.00	.85	1.20	.47	1.46	.36	1.33	1.19	.13	.83	1.30	0.00
	GVW	2.7	4.5	4.1	31.5	33.8	28.0	34.5	24.0	51.0	69.9	26.8	49.9	74.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9