

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	21	3,775	2,364	2	65	104	16	69	233	180	3	5	80	0
	Flex	.00	.00	.00	.99	.66	.41	.59	.54	.79	.61	.27	1.06	.77	0.00
	Rigid	.00	.00	.00	1.27	.74	.64	.83	.71	1.43	1.31	.39	1.37	1.37	0.00
	GVW	2.4	4.1	4.2	32.9	20.4	28.4	33.0	26.2	53.3	62.9	32.4	50.5	63.9	0.0
N	Num	15	1,878	1,190	2	35	42	7	45	138	101	2	2	23	0
	Flex	.00	.00	.00	1.08	.47	.59	.44	.38	.78	.60	.29	.63	.87	0.00
	Rigid	.00	.00	.00	1.37	.49	1.02	.70	.52	1.41	1.22	.31	.81	1.48	0.00
	GVW	2.0	3.9	4.2	33.2	18.3	33.5	34.2	27.2	54.6	58.6	32.8	57.8	68.3	0.0
S	Num	6	1,897	1,174	2	30	62	8	25	95	79	2	3	57	0
	Flex	.00	.00	.00	.70	.87	.31	.71	.83	.82	.64	.27	1.15	.71	0.00
	Rigid	.00	.00	.00	.87	1.03	.43	.94	1.02	1.46	1.45	.48	1.47	1.31	0.00
	GVW	2.8	4.3	4.2	29.6	22.9	25.7	31.4	24.0	51.3	68.8	33.0	45.0	62.5	0.0
N Lane1	Num	15	1,878	1,190	2	35	42	7	45	138	101	2	2	23	0
	Flex	.00	.00	.00	1.08	.47	.59	.44	.38	.78	.60	.29	.63	.87	0.00
	Rigid	.00	.00	.00	1.37	.49	1.02	.70	.52	1.41	1.22	.31	.81	1.48	0.00
	GVW	2.0	3.9	4.2	33.2	18.3	33.5	34.2	27.2	54.6	58.6	32.8	57.8	68.3	0.0
S Lane1	Num	6	1,897	1,174	2	30	62	8	25	95	79	2	3	57	0
	Flex	.00	.00	.00	.70	.87	.31	.71	.83	.82	.64	.27	1.15	.71	0.00
	Rigid	.00	.00	.00	.87	1.03	.43	.94	1.02	1.46	1.45	.48	1.47	1.31	0.00
	GVW	2.8	4.3	4.2	29.6	22.9	25.7	31.4	24.0	51.3	68.8	33.0	45.0	62.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9