

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	29	4,339	2,649	2	67	121	19	94	233	171	4	5	107	0
	Flex	.00	.00	.00	.66	.63	.44	.59	.42	.81	.60	.82	.68	.59	0.00
	Rigid	.00	.00	.00	1.02	.69	.72	.79	.55	1.47	1.25	1.01	.84	1.05	0.00
	GVW	2.4	4.2	4.2	31.8	20.7	27.7	32.1	25.3	53.1	60.1	30.6	44.4	58.2	0.0
N	Num	20	2,137	1,323	2	39	51	7	61	150	96	2	2	27	0
	Flex	.00	.00	.00	.74	.58	.70	.66	.44	.86	.62	.44	.61	1.01	0.00
	Rigid	.00	.00	.00	1.14	.61	1.24	.93	.58	1.56	1.24	.55	.74	1.78	0.00
	GVW	2.0	4.1	4.2	34.6	19.2	33.9	36.2	27.0	55.9	59.9	31.4	51.7	75.8	0.0
S	Num	10	2,202	1,325	1	28	70	11	33	84	74	4	3	80	0
	Flex	.00	.00	.00	.66	.68	.27	.55	.41	.73	.59	.99	.89	.48	0.00
	Rigid	.00	.00	.00	1.00	.80	.38	.70	.53	1.31	1.30	1.22	1.10	.89	0.00
	GVW	2.6	4.4	4.2	29.9	22.6	23.9	28.9	22.2	48.1	61.0	31.3	40.4	53.3	0.0
N Lane1	Num	20	2,137	1,323	2	39	51	7	61	150	96	2	2	27	0
	Flex	.00	.00	.00	.74	.58	.70	.66	.44	.86	.62	.44	.61	1.01	0.00
	Rigid	.00	.00	.00	1.14	.61	1.24	.93	.58	1.56	1.24	.55	.74	1.78	0.00
	GVW	2.0	4.1	4.2	34.6	19.2	33.9	36.2	27.0	55.9	59.9	31.4	51.7	75.8	0.0
S Lane1	Num	10	2,202	1,325	1	28	70	11	33	84	74	4	3	80	0
	Flex	.00	.00	.00	.66	.68	.27	.55	.41	.73	.59	.99	.89	.48	0.00
	Rigid	.00	.00	.00	1.00	.80	.38	.70	.53	1.31	1.30	1.22	1.10	.89	0.00
	GVW	2.6	4.4	4.2	29.9	22.6	23.9	28.9	22.2	48.1	61.0	31.3	40.4	53.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9