

Idaho Transportation Department

Monthly WIM Distribution for Aug-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	24	4,398	2,692	3	74	128	19	91	238	171	4	5	92	0
	Flex	.00	.00	.00	1.18	.67	.48	.62	.45	.80	.53	.97	1.05	.60	0.00
	Rigid	.00	.00	.00	1.77	.75	.78	.85	.60	1.44	1.10	1.21	1.32	1.09	0.00
	GVW	2.3	4.2	4.2	40.3	20.8	30.0	34.8	25.5	53.5	59.9	32.1	54.2	60.2	0.0
N	Num	16	2,178	1,357	2	41	54	7	56	151	100	2	2	24	0
	Flex	.00	.00	.00	1.48	.44	.69	.64	.34	.80	.56	.68	.91	1.06	0.00
	Rigid	.00	.00	.00	2.25	.45	1.19	.95	.47	1.45	1.15	.94	1.12	1.77	0.00
	GVW	2.2	4.1	4.2	43.8	18.6	34.9	37.9	26.0	55.1	59.3	37.7	56.4	72.6	0.0
S	Num	7	2,220	1,335	1	33	75	12	35	87	71	3	3	68	0
	Flex	.00	.00	.00	.73	.94	.35	.53	.61	.79	.51	1.16	.84	.47	0.00
	Rigid	.00	.00	.00	1.12	1.12	.50	.71	.77	1.43	1.09	1.42	1.09	.90	0.00
	GVW	2.4	4.4	4.2	37.0	23.4	26.8	32.8	24.1	50.6	61.6	30.3	47.9	56.8	0.0
N Lane1	Num	16	2,178	1,357	2	41	54	7	56	151	100	2	2	24	0
	Flex	.00	.00	.00	1.48	.44	.69	.64	.34	.80	.56	.68	.91	1.06	0.00
	Rigid	.00	.00	.00	2.25	.45	1.19	.95	.47	1.45	1.15	.94	1.12	1.77	0.00
	GVW	2.2	4.1	4.2	43.8	18.6	34.9	37.9	26.0	55.1	59.3	37.7	56.4	72.6	0.0
S Lane1	Num	7	2,220	1,335	1	33	75	12	35	87	71	3	3	68	0
	Flex	.00	.00	.00	.73	.94	.35	.53	.61	.79	.51	1.16	.84	.47	0.00
	Rigid	.00	.00	.00	1.12	1.12	.50	.71	.77	1.43	1.09	1.42	1.09	.90	0.00
	GVW	2.4	4.4	4.2	37.0	23.4	26.8	32.8	24.1	50.6	61.6	30.3	47.9	56.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9