

Idaho Transportation Department

Monthly WIM Distribution for Nov-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	2,747	1,962	2	42	62	9	33	162	144	5	7	125	0
	Flex	.00	.00	.00	.44	.38	.30	.18	.16	.44	.32	.31	.38	.27	0.00
	Rigid	.00	.00	.00	.70	.40	.45	.29	.22	.74	.65	.38	.51	.49	0.00
	GVW	2.6	4.5	3.9	30.8	18.8	30.2	33.6	26.1	48.0	56.2	32.7	50.7	65.0	0.0
N	Num	11	1,343	976	1	26	34	4	22	111	92	2	2	18	0
	Flex	.00	.00	.00	.35	.36	.33	.20	.16	.46	.34	.14	.51	.51	0.00
	Rigid	.00	.00	.00	.52	.36	.52	.41	.22	.80	.68	.23	.66	.84	0.00
	GVW	2.5	4.3	4.2	30.5	18.2	30.7	36.0	26.4	50.6	55.0	34.9	56.1	63.8	0.0
S	Num	2	1,404	986	1	16	28	5	12	50	53	4	5	108	0
	Flex	.00	.00	.00	.58	.41	.25	.17	.17	.34	.30	.31	.36	.23	0.00
	Rigid	.00	.00	.00	.96	.45	.33	.23	.22	.52	.60	.37	.50	.43	0.00
	GVW	3.6	4.7	3.7	30.3	20.0	29.3	32.3	25.5	41.2	58.0	30.7	50.0	65.1	0.0
N Lane1	Num	11	1,343	976	1	26	34	4	22	111	92	2	2	18	0
	Flex	.00	.00	.00	.35	.36	.33	.20	.16	.46	.34	.14	.51	.51	0.00
	Rigid	.00	.00	.00	.52	.36	.52	.41	.22	.80	.68	.23	.66	.84	0.00
	GVW	2.5	4.3	4.2	30.5	18.2	30.7	36.0	26.4	50.6	55.0	34.9	56.1	63.8	0.0
S Lane1	Num	2	1,404	986	1	16	28	5	12	50	53	4	5	108	0
	Flex	.00	.00	.00	.58	.41	.25	.17	.17	.34	.30	.31	.36	.23	0.00
	Rigid	.00	.00	.00	.96	.45	.33	.23	.22	.52	.60	.37	.50	.43	0.00
	GVW	3.6	4.7	3.7	30.3	20.0	29.3	32.3	25.5	41.2	58.0	30.7	50.0	65.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9