

Idaho Transportation Department

Monthly WIM Distribution for Dec-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	356	1,209	2	26	46	4	28	102	94	4	5	99	0
	Flex	.00	.00	.00	.62	.29	.35	.29	.14	.35	.27	.20	.41	.25	0.00
	Rigid	.00	.00	.00	.85	.29	.49	.36	.20	.58	.52	.36	.54	.46	0.00
	GVW	2.5	3.7	3.8	39.9	18.9	31.4	37.0	27.3	47.0	53.3	39.2	51.1	65.9	0.0
N	Num	12	176	599	2	16	26	1	19	73	61	1	3	14	0
	Flex	.00	.00	.00	.43	.31	.31	.34	.13	.41	.32	.16	.46	.61	0.00
	Rigid	.00	.00	.00	.62	.30	.46	.47	.21	.69	.64	.38	.60	1.11	0.00
	GVW	2.5	3.6	4.1	37.4	18.9	30.3	36.0	27.6	49.8	56.0	51.5	54.6	72.2	0.0
S	Num	0	1,412	915	1	10	21	4	9	37	34	4	3	84	0
	Flex	0.00	.00	.00	.81	.24	.41	.28	.15	.23	.20	.22	.36	.21	0.00
	Rigid	0.00	.00	.00	1.09	.25	.56	.34	.18	.33	.38	.41	.51	.40	0.00
	GVW	0.0	4.7	3.5	42.5	18.7	33.2	37.3	26.5	39.6	50.4	39.1	51.5	66.0	0.0
N Lane1	Num	12	176	599	2	16	26	1	19	73	61	1	3	14	0
	Flex	.00	.00	.00	.43	.31	.31	.34	.13	.41	.32	.16	.46	.61	0.00
	Rigid	.00	.00	.00	.62	.30	.46	.47	.21	.69	.64	.38	.60	1.11	0.00
	GVW	2.5	3.6	4.1	37.4	18.9	30.3	36.0	27.6	49.8	56.0	51.5	54.6	72.2	0.0
S Lane1	Num	0	1,412	915	1	10	21	4	9	37	34	4	3	84	0
	Flex	0.00	.00	.00	.81	.24	.41	.28	.15	.23	.20	.22	.36	.21	0.00
	Rigid	0.00	.00	.00	1.09	.25	.56	.34	.18	.33	.38	.41	.51	.40	0.00
	GVW	0.0	4.7	3.5	42.5	18.7	33.2	37.3	26.5	39.6	50.4	39.1	51.5	66.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2017

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9