

Idaho Transportation Department

Monthly WIM Distribution for Nov-2018

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	38	3,040	2,102	2	60	102	14	51	232	162	5	4	35	0
	Flex	.00	.00	.00	.57	.47	.42	.33	.21	.58	.46	.36	.41	.60	0.00
	Rigid	.00	.00	.00	.85	.47	.67	.60	.36	.99	1.03	.59	.51	1.04	0.00
	GVW	2.4	4.0	4.5	37.0	19.4	32.4	39.5	30.9	52.8	68.7	48.2	50.2	70.1	0.0
N	Num	20	1,510	1,051	1	30	52	8	26	112	76	4	2	18	0
	Flex	.00	.00	.00	.47	.50	.54	.20	.18	.54	.41	.34	.69	.45	0.00
	Rigid	.00	.00	.00	.69	.51	.92	.47	.31	.94	.83	.60	.88	.77	0.00
	GVW	2.4	4.0	4.5	35.4	19.5	34.8	37.7	30.0	52.9	58.7	51.5	61.3	62.4	0.0
S	Num	21	1,530	1,051	1	30	51	5	25	120	86	2	2	17	0
	Flex	.00	.00	.00	.53	.43	.33	.41	.23	.61	.49	.39	.21	.72	0.00
	Rigid	.00	.00	.00	.78	.43	.49	.69	.40	1.05	1.18	.47	.24	1.26	0.00
	GVW	2.5	4.1	4.6	34.4	19.2	30.8	39.8	31.7	52.7	77.2	35.1	42.5	76.0	0.0
N Lane1	Num	20	1,510	1,051	1	30	52	8	26	112	76	4	2	18	0
	Flex	.00	.00	.00	.47	.50	.54	.20	.18	.54	.41	.34	.69	.45	0.00
	Rigid	.00	.00	.00	.69	.51	.92	.47	.31	.94	.83	.60	.88	.77	0.00
	GVW	2.4	4.0	4.5	35.4	19.5	34.8	37.7	30.0	52.9	58.7	51.5	61.3	62.4	0.0
S Lane1	Num	21	1,530	1,051	1	30	51	5	25	120	86	2	2	17	0
	Flex	.00	.00	.00	.53	.43	.33	.41	.23	.61	.49	.39	.21	.72	0.00
	Rigid	.00	.00	.00	.78	.43	.49	.69	.40	1.05	1.18	.47	.24	1.26	0.00
	GVW	2.5	4.1	4.6	34.4	19.2	30.8	39.8	31.7	52.7	77.2	35.1	42.5	76.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2018

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9