

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	39	2,626	1,743	2	50	102	13	40	211	178	3	3	31	0
	Flex	.00	.00	.00	.52	.56	.45	.20	.22	.63	.45	.42	.41	.66	0.00
	Rigid	.00	.00	.00	.85	.57	.74	.51	.38	1.10	1.02	.77	.49	1.24	0.00
	GVW	2.4	3.9	4.5	34.6	20.4	33.1	39.4	31.3	54.1	68.3	49.5	51.4	74.1	0.0
N	Num	23	1,303	870	1	24	52	8	22	106	81	2	2	15	0
	Flex	.00	.00	.00	.43	.55	.52	.17	.20	.60	.38	.46	.65	.55	0.00
	Rigid	.00	.00	.00	.68	.56	.88	.46	.34	1.06	.74	.85	.83	1.00	0.00
	GVW	2.5	3.9	4.5	31.0	20.3	34.6	38.5	30.5	54.6	54.4	51.9	60.9	68.3	0.0
S	Num	16	1,323	873	2	26	50	5	19	105	97	1	2	16	0
	Flex	.00	.00	.00	.54	.55	.40	.22	.25	.66	.52	.17	.26	.73	0.00
	Rigid	.00	.00	.00	.90	.56	.64	.59	.43	1.13	1.26	.34	.29	1.42	0.00
	GVW	2.2	4.0	4.6	35.5	20.4	32.0	40.1	31.9	53.5	80.9	41.1	46.1	78.8	0.0
N Lane1	Num	23	1,303	870	1	24	52	8	22	106	81	2	2	15	0
	Flex	.00	.00	.00	.43	.55	.52	.17	.20	.60	.38	.46	.65	.55	0.00
	Rigid	.00	.00	.00	.68	.56	.88	.46	.34	1.06	.74	.85	.83	1.00	0.00
	GVW	2.5	3.9	4.5	31.0	20.3	34.6	38.5	30.5	54.6	54.4	51.9	60.9	68.3	0.0
S Lane1	Num	16	1,323	873	2	26	50	5	19	105	97	1	2	16	0
	Flex	.00	.00	.00	.54	.55	.40	.22	.25	.66	.52	.17	.26	.73	0.00
	Rigid	.00	.00	.00	.90	.56	.64	.59	.43	1.13	1.26	.34	.29	1.42	0.00
	GVW	2.2	4.0	4.6	35.5	20.4	32.0	40.1	31.9	53.5	80.9	41.1	46.1	78.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9