

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2019

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	37	2,452	1,649	2	50	97	7	37	214	186	3	3	32	0
	Flex	.00	.00	.00	.61	.61	.49	.32	.32	.70	.51	.77	.44	.76	0.00
	Rigid	.00	.00	.00	.99	.62	.78	.69	.51	1.25	1.18	1.14	.52	1.34	0.00
	GVW	2.2	4.0	4.4	32.8	20.8	32.9	41.7	33.7	55.1	69.3	46.0	51.7	70.9	0.0
N	Num	19	1,218	822	1	24	53	4	18	106	88	2	1	16	0
	Flex	.00	.00	.00	.60	.49	.42	.29	.25	.62	.39	.70	.75	.66	0.00
	Rigid	.00	.00	.00	.92	.49	.69	.59	.35	1.11	.76	1.12	.97	1.14	0.00
	GVW	2.2	3.9	4.4	31.5	19.6	32.3	40.1	31.1	54.9	53.5	45.4	60.1	67.9	0.0
S	Num	23	1,234	827	2	26	44	4	20	109	99	2	2	17	0
	Flex	.00	.00	.00	.64	.70	.58	.28	.36	.79	.61	.67	.23	.85	0.00
	Rigid	.00	.00	.00	1.04	.72	.92	.62	.60	1.38	1.52	.92	.26	1.51	0.00
	GVW	2.4	4.1	4.3	35.4	21.6	34.0	38.2	35.0	55.3	82.9	45.6	45.3	74.2	0.0
N Lane1	Num	19	1,218	822	1	24	53	4	18	106	88	2	1	16	0
	Flex	.00	.00	.00	.60	.49	.42	.29	.25	.62	.39	.70	.75	.66	0.00
	Rigid	.00	.00	.00	.92	.49	.69	.59	.35	1.11	.76	1.12	.97	1.14	0.00
	GVW	2.2	3.9	4.4	31.5	19.6	32.3	40.1	31.1	54.9	53.5	45.4	60.1	67.9	0.0
S Lane1	Num	23	1,234	827	2	26	44	4	20	109	99	2	2	17	0
	Flex	.00	.00	.00	.64	.70	.58	.28	.36	.79	.61	.67	.23	.85	0.00
	Rigid	.00	.00	.00	1.04	.72	.92	.62	.60	1.38	1.52	.92	.26	1.51	0.00
	GVW	2.4	4.1	4.3	35.4	21.6	34.0	38.2	35.0	55.3	82.9	45.6	45.3	74.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2019

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9