

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2019

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	5	2,992	1,915	2	48	38	4	33	240	198	2	3	33	0
	Flex	.00	.00	.00	.47	.44	.37	.44	.25	.69	.44	.65	.46	.70	0.00
	Rigid	.00	.00	.00	.75	.44	.53	.64	.30	1.19	1.02	.83	.53	1.25	0.00
	GVW	2.3	3.9	4.4	26.8	19.7	30.1	35.4	27.1	54.0	67.6	45.4	48.8	72.7	0.0
N	Num	4	1,493	960	1	24	19	2	18	115	96	1	2	15	0
	Flex	.00	.00	.00	.44	.45	.43	.47	.26	.65	.38	.37	.76	.59	0.00
	Rigid	.00	.00	.00	.65	.46	.64	.67	.31	1.13	.74	.53	.93	1.01	0.00
	GVW	2.5	3.9	4.4	21.7	19.7	32.0	35.9	26.7	53.9	53.3	42.0	56.4	65.7	0.0
S	Num	3	1,498	955	2	24	19	2	15	125	101	1	2	18	0
	Flex	.00	.00	.00	.46	.42	.32	.34	.22	.73	.49	.88	.22	.81	0.00
	Rigid	.00	.00	.00	.78	.42	.45	.51	.29	1.25	1.27	.93	.23	1.48	0.00
	GVW	2.2	3.9	4.5	31.4	19.6	28.9	32.9	27.5	54.1	81.0	41.8	44.7	79.2	0.0
N Lane1	Num	4	1,493	960	1	24	19	2	18	115	96	1	2	15	0
	Flex	.00	.00	.00	.44	.45	.43	.47	.26	.65	.38	.37	.76	.59	0.00
	Rigid	.00	.00	.00	.65	.46	.64	.67	.31	1.13	.74	.53	.93	1.01	0.00
	GVW	2.5	3.9	4.4	21.7	19.7	32.0	35.9	26.7	53.9	53.3	42.0	56.4	65.7	0.0
S Lane1	Num	3	1,498	955	2	24	19	2	15	125	101	1	2	18	0
	Flex	.00	.00	.00	.46	.42	.32	.34	.22	.73	.49	.88	.22	.81	0.00
	Rigid	.00	.00	.00	.78	.42	.45	.51	.29	1.25	1.27	.93	.23	1.48	0.00
	GVW	2.2	3.9	4.5	31.4	19.6	28.9	32.9	27.5	54.1	81.0	41.8	44.7	79.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2019

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9