

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	41	4,501	2,851	3	83	140	20	107	272	187	3	5	42	0
	Flex	.00	.00	.00	.57	.62	.56	.57	.38	.73	.56	.60	.58	.86	0.00
	Rigid	.00	.00	.00	.84	.65	.96	.89	.52	1.27	1.27	.81	.73	1.49	0.00
	GVW	2.4	4.0	4.5	32.3	20.0	31.9	39.3	26.2	53.1	70.2	39.8	49.2	72.5	0.0
N	Num	29	2,229	1,414	2	43	63	13	58	134	93	3	3	23	0
	Flex	.00	.00	.00	.76	.74	.87	.66	.41	.78	.54	.70	.62	.86	0.00
	Rigid	.00	.00	.00	1.10	.78	1.60	1.01	.57	1.37	1.12	.97	.80	1.49	0.00
	GVW	2.4	3.9	4.4	35.1	20.3	35.3	40.7	27.1	54.9	60.0	43.5	53.3	70.0	0.0
S	Num	13	2,272	1,437	2	40	77	7	49	137	94	2	3	19	0
	Flex	.00	.00	.00	.49	.49	.31	.49	.36	.69	.57	.45	.53	.79	0.00
	Rigid	.00	.00	.00	.75	.50	.44	.75	.46	1.18	1.41	.55	.64	1.40	0.00
	GVW	2.3	4.1	4.5	31.3	19.6	29.2	37.0	25.0	51.2	80.0	33.8	46.8	73.7	0.0
N Lane1	Num	29	2,229	1,414	2	43	63	13	58	134	93	3	3	23	0
	Flex	.00	.00	.00	.76	.74	.87	.66	.41	.78	.54	.70	.62	.86	0.00
	Rigid	.00	.00	.00	1.10	.78	1.60	1.01	.57	1.37	1.12	.97	.80	1.49	0.00
	GVW	2.4	3.9	4.4	35.1	20.3	35.3	40.7	27.1	54.9	60.0	43.5	53.3	70.0	0.0
S Lane1	Num	13	2,272	1,437	2	40	77	7	49	137	94	2	3	19	0
	Flex	.00	.00	.00	.49	.49	.31	.49	.36	.69	.57	.45	.53	.79	0.00
	Rigid	.00	.00	.00	.75	.50	.44	.75	.46	1.18	1.41	.55	.64	1.40	0.00
	GVW	2.3	4.1	4.5	31.3	19.6	29.2	37.0	25.0	51.2	80.0	33.8	46.8	73.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9