

Idaho Transportation Department

Monthly WIM Distribution for Aug-2019

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	34	4,529	2,853	2	81	126	17	99	299	240	3	6	43	0
	Flex	.00	.00	.00	.80	.61	.51	.50	.36	.68	.57	.89	.37	.79	0.00
	Rigid	.00	.00	.00	1.09	.64	.84	.83	.48	1.19	1.36	1.17	.47	1.36	0.00
	GVW	2.2	4.0	4.5	33.8	20.0	32.9	38.7	25.9	52.2	71.0	42.9	46.4	71.3	0.0
N	Num	22	2,242	1,433	2	42	59	10	53	136	131	2	3	22	0
	Flex	.00	.00	.00	.74	.76	.75	.52	.37	.77	.65	1.05	.54	.75	0.00
	Rigid	.00	.00	.00	.93	.80	1.28	.89	.50	1.37	1.57	1.42	.71	1.27	0.00
	GVW	2.3	3.9	4.4	27.8	20.7	35.8	39.4	26.0	54.6	70.0	47.3	54.0	66.5	0.0
S	Num	12	2,287	1,420	2	39	67	7	45	162	109	2	3	21	0
	Flex	.00	.00	.00	.57	.46	.32	.52	.34	.61	.48	.44	.28	.80	0.00
	Rigid	.00	.00	.00	.82	.46	.47	.79	.45	1.05	1.12	.59	.33	1.39	0.00
	GVW	2.2	4.0	4.5	32.9	19.2	30.4	38.5	25.9	50.1	72.1	37.0	41.6	74.8	0.0
N Lane1	Num	22	2,242	1,433	2	42	59	10	53	136	131	2	3	22	0
	Flex	.00	.00	.00	.74	.76	.75	.52	.37	.77	.65	1.05	.54	.75	0.00
	Rigid	.00	.00	.00	.93	.80	1.28	.89	.50	1.37	1.57	1.42	.71	1.27	0.00
	GVW	2.3	3.9	4.4	27.8	20.7	35.8	39.4	26.0	54.6	70.0	47.3	54.0	66.5	0.0
S Lane1	Num	12	2,287	1,420	2	39	67	7	45	162	109	2	3	21	0
	Flex	.00	.00	.00	.57	.46	.32	.52	.34	.61	.48	.44	.28	.80	0.00
	Rigid	.00	.00	.00	.82	.46	.47	.79	.45	1.05	1.12	.59	.33	1.39	0.00
	GVW	2.2	4.0	4.5	32.9	19.2	30.4	38.5	25.9	50.1	72.1	37.0	41.6	74.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2019

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9