

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	33	3,786	2,530	2	80	131	13	77	260	197	3	5	55	0
	Flex	.00	.00	.00	.69	.54	.46	.57	.35	.64	.50	.76	.41	.74	0.00
	Rigid	.00	.00	.00	1.06	.55	.72	.92	.49	1.10	1.12	.92	.50	1.34	0.00
	GVW	2.2	3.9	4.5	35.4	19.4	31.7	39.4	27.9	52.2	68.4	38.8	49.1	74.3	0.0
N	Num	22	1,870	1,254	1	41	57	9	43	130	92	2	3	31	0
	Flex	.00	.00	.00	.59	.60	.59	.55	.34	.60	.46	.78	.59	.64	0.00
	Rigid	.00	.00	.00	.87	.63	.98	.87	.48	1.03	.96	.99	.73	1.09	0.00
	GVW	2.3	3.9	4.5	33.3	19.6	33.4	39.4	28.4	51.8	58.5	42.1	57.8	67.9	0.0
S	Num	11	1,916	1,275	1	39	74	5	33	129	105	2	3	24	0
	Flex	.00	.00	.00	.72	.46	.36	.73	.37	.69	.52	.49	.34	.84	0.00
	Rigid	.00	.00	.00	1.15	.46	.53	1.08	.49	1.19	1.28	.57	.40	1.55	0.00
	GVW	2.2	3.9	4.5	37.6	19.1	30.6	39.0	27.2	52.6	77.2	32.3	44.4	80.0	0.0
N Lane1	Num	22	1,870	1,254	1	41	57	9	43	130	92	2	3	31	0
	Flex	.00	.00	.00	.59	.60	.59	.55	.34	.60	.46	.78	.59	.64	0.00
	Rigid	.00	.00	.00	.87	.63	.98	.87	.48	1.03	.96	.99	.73	1.09	0.00
	GVW	2.3	3.9	4.5	33.3	19.6	33.4	39.4	28.4	51.8	58.5	42.1	57.8	67.9	0.0
S Lane1	Num	11	1,916	1,275	1	39	74	5	33	129	105	2	3	24	0
	Flex	.00	.00	.00	.72	.46	.36	.73	.37	.69	.52	.49	.34	.84	0.00
	Rigid	.00	.00	.00	1.15	.46	.53	1.08	.49	1.19	1.28	.57	.40	1.55	0.00
	GVW	2.2	3.9	4.5	37.6	19.1	30.6	39.0	27.2	52.6	77.2	32.3	44.4	80.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9