

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2019

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	39	3,494	2,396	3	70	120	10	65	234	199	4	6	47	0
	Flex	.00	.00	.00	.58	.54	.41	.34	.27	.59	.42	.30	.48	.65	0.00
	Rigid	.00	.00	.00	.87	.55	.65	.68	.44	1.01	.98	.43	.57	1.18	0.00
	GVW	2.3	3.9	4.5	32.3	20.0	30.6	38.2	31.3	51.6	67.9	37.5	50.2	69.5	0.0
N	Num	29	1,742	1,195	1	35	53	6	40	119	97	3	3	24	0
	Flex	.00	.00	.00	.48	.51	.52	.28	.24	.52	.37	.25	.54	.47	0.00
	Rigid	.00	.00	.00	.71	.52	.89	.53	.44	.88	.74	.43	.63	.89	0.00
	GVW	2.4	3.9	4.5	30.1	19.6	32.3	36.0	32.9	50.8	55.8	43.6	55.3	63.2	0.0
S	Num	10	1,753	1,201	2	35	67	5	25	115	102	2	3	23	0
	Flex	.00	.00	.00	.57	.56	.32	.43	.32	.66	.46	.91	.41	.83	0.00
	Rigid	.00	.00	.00	.88	.57	.47	.87	.45	1.12	1.18	.91	.49	1.49	0.00
	GVW	2.3	4.0	4.5	30.7	20.3	29.4	40.9	29.5	52.3	78.9	36.9	45.8	75.2	0.0
N Lane1	Num	29	1,742	1,195	1	35	53	6	40	119	97	3	3	24	0
	Flex	.00	.00	.00	.48	.51	.52	.28	.24	.52	.37	.25	.54	.47	0.00
	Rigid	.00	.00	.00	.71	.52	.89	.53	.44	.88	.74	.43	.63	.89	0.00
	GVW	2.4	3.9	4.5	30.1	19.6	32.3	36.0	32.9	50.8	55.8	43.6	55.3	63.2	0.0
S Lane1	Num	10	1,753	1,201	2	35	67	5	25	115	102	2	3	23	0
	Flex	.00	.00	.00	.57	.56	.32	.43	.32	.66	.46	.91	.41	.83	0.00
	Rigid	.00	.00	.00	.88	.57	.47	.87	.45	1.12	1.18	.91	.49	1.49	0.00
	GVW	2.3	4.0	4.5	30.7	20.3	29.4	40.9	29.5	52.3	78.9	36.9	45.8	75.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2019

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9