

Idaho Transportation Department

Monthly WIM Distribution for Dec-2019

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	23	2,922	1,906	2	46	80	5	40	185	159	2	4	30	0
	Flex	.00	.00	.00	.52	.52	.46	.30	.23	.60	.43	.37	.34	.58	0.00
	Rigid	.00	.00	.00	.73	.53	.71	.68	.40	1.03	.99	.57	.42	1.03	0.00
	GVW	2.8	4.1	4.5	31.2	19.8	32.5	39.2	31.3	53.2	68.5	42.1	47.9	68.8	0.0
N	Num	21	1,458	954	1	25	36	3	25	94	76	2	2	15	0
	Flex	.00	.00	.00	.35	.47	.57	.20	.22	.54	.34	.37	.50	.43	0.00
	Rigid	.00	.00	.00	.47	.47	.95	.51	.39	.92	.64	.58	.59	.78	0.00
	GVW	2.8	4.1	4.4	26.3	19.7	34.5	39.4	32.2	52.9	54.0	42.9	55.4	64.2	0.0
S	Num	5	1,464	953	1	21	43	3	16	91	84	1	2	15	0
	Flex	.00	.00	.00	.83	.57	.37	.44	.27	.66	.50	.23	.30	.71	0.00
	Rigid	.00	.00	.00	1.18	.59	.51	.92	.45	1.13	1.28	.30	.36	1.29	0.00
	GVW	2.6	4.0	4.6	37.3	19.8	31.1	43.3	31.0	53.2	81.1	33.2	43.8	73.7	0.0
N Lane1	Num	21	1,458	954	1	25	36	3	25	94	76	2	2	15	0
	Flex	.00	.00	.00	.35	.47	.57	.20	.22	.54	.34	.37	.50	.43	0.00
	Rigid	.00	.00	.00	.47	.47	.95	.51	.39	.92	.64	.58	.59	.78	0.00
	GVW	2.8	4.1	4.4	26.3	19.7	34.5	39.4	32.2	52.9	54.0	42.9	55.4	64.2	0.0
S Lane1	Num	5	1,464	953	1	21	43	3	16	91	84	1	2	15	0
	Flex	.00	.00	.00	.83	.57	.37	.44	.27	.66	.50	.23	.30	.71	0.00
	Rigid	.00	.00	.00	1.18	.59	.51	.92	.45	1.13	1.28	.30	.36	1.29	0.00
	GVW	2.6	4.0	4.6	37.3	19.8	31.1	43.3	31.0	53.2	81.1	33.2	43.8	73.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2019

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9