

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2020

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	30	2,475	1,775	2	53	87	6	38	208	176	3	3	32	0
	Flex	.00	.00	.00	.45	.56	.43	.21	.25	.62	.47	.79	.50	.59	0.00
	Rigid	.00	.00	.00	.61	.56	.68	.48	.40	1.08	1.05	1.11	.63	1.04	0.00
	GVW	2.5	4.1	4.5	29.0	20.7	32.4	36.8	32.2	54.0	69.7	38.0	49.2	67.6	0.0
N	Num	25	1,234	886	1	26	42	3	21	102	83	3	2	16	0
	Flex	.00	.00	.00	.46	.47	.50	.18	.21	.53	.36	1.06	.58	.38	0.00
	Rigid	.00	.00	.00	.61	.47	.85	.41	.36	.92	.69	1.47	.70	.67	0.00
	GVW	2.5	4.2	4.4	30.2	19.9	34.2	35.4	32.2	53.2	54.9	40.3	57.4	60.2	0.0
S	Num	6	1,241	889	1	26	45	3	16	106	93	1	2	17	0
	Flex	.00	.00	.00	.46	.64	.37	.20	.28	.70	.56	.44	.53	.79	0.00
	Rigid	.00	.00	.00	.68	.65	.53	.49	.45	1.24	1.36	.62	.71	1.38	0.00
	GVW	2.4	4.1	4.5	30.5	21.4	30.9	35.6	31.8	54.6	82.4	35.8	45.8	74.2	0.0
N Lane1	Num	25	1,234	886	1	26	42	3	21	102	83	3	2	16	0
	Flex	.00	.00	.00	.46	.47	.50	.18	.21	.53	.36	1.06	.58	.38	0.00
	Rigid	.00	.00	.00	.61	.47	.85	.41	.36	.92	.69	1.47	.70	.67	0.00
	GVW	2.5	4.2	4.4	30.2	19.9	34.2	35.4	32.2	53.2	54.9	40.3	57.4	60.2	0.0
S Lane1	Num	6	1,241	889	1	26	45	3	16	106	93	1	2	17	0
	Flex	.00	.00	.00	.46	.64	.37	.20	.28	.70	.56	.44	.53	.79	0.00
	Rigid	.00	.00	.00	.68	.65	.53	.49	.45	1.24	1.36	.62	.71	1.38	0.00
	GVW	2.4	4.1	4.5	30.5	21.4	30.9	35.6	31.8	54.6	82.4	35.8	45.8	74.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2020

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9