

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	21	3,020	1,920	2	58	74	7	38	230	181	2	4	31	0
	Flex	.00	.00	.00	.54	.42	.45	.35	.24	.60	.44	.51	.25	.58	0.00
	Rigid	.00	.00	.00	.78	.42	.71	.62	.40	1.03	.98	.69	.29	1.04	0.00
	GVW	3.0	4.0	4.5	34.8	19.5	32.8	38.8	31.7	53.6	69.2	40.1	44.7	69.6	0.0
N	Num	17	1,507	958	1	29	38	3	21	111	86	2	2	14	0
	Flex	.00	.00	.00	.59	.36	.54	.32	.22	.54	.36	.55	.30	.39	0.00
	Rigid	.00	.00	.00	.93	.36	.91	.53	.35	.93	.70	.77	.36	.72	0.00
	GVW	3.1	4.1	4.4	35.9	19.1	34.7	33.6	31.1	52.7	55.2	43.2	49.2	59.7	0.0
S	Num	8	1,512	962	2	30	36	4	17	119	96	2	2	17	0
	Flex	.00	.00	.00	.52	.48	.36	.36	.26	.65	.50	.24	.15	.70	0.00
	Rigid	.00	.00	.00	.73	.48	.53	.69	.45	1.12	1.22	.27	.17	1.26	0.00
	GVW	2.4	3.9	4.6	32.6	19.9	31.1	42.6	31.8	54.3	81.5	33.8	37.9	76.6	0.0
N Lane1	Num	17	1,507	958	1	29	38	3	21	111	86	2	2	14	0
	Flex	.00	.00	.00	.59	.36	.54	.32	.22	.54	.36	.55	.30	.39	0.00
	Rigid	.00	.00	.00	.93	.36	.91	.53	.35	.93	.70	.77	.36	.72	0.00
	GVW	3.1	4.1	4.4	35.9	19.1	34.7	33.6	31.1	52.7	55.2	43.2	49.2	59.7	0.0
S Lane1	Num	8	1,512	962	2	30	36	4	17	119	96	2	2	17	0
	Flex	.00	.00	.00	.52	.48	.36	.36	.26	.65	.50	.24	.15	.70	0.00
	Rigid	.00	.00	.00	.73	.48	.53	.69	.45	1.12	1.22	.27	.17	1.26	0.00
	GVW	2.4	3.9	4.6	32.6	19.9	31.1	42.6	31.8	54.3	81.5	33.8	37.9	76.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9