

Idaho Transportation Department

Monthly WIM Distribution for Mar-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	7	2,475	1,718	2	45	35	2	31	254	174	2	4	35	0
	Flex	.00	.00	.00	.21	.37	.45	.67	.25	.66	.42	.25	.32	.56	0.00
	Rigid	.00	.00	.00	.26	.37	.70	.82	.30	1.13	.95	.27	.39	.97	0.00
	GVW	2.1	3.9	4.5	22.2	18.8	31.9	34.6	26.6	53.9	67.7	27.3	44.2	68.5	0.0
N	Num	6	1,253	867	1	24	16	2	19	125	82	2	2	17	0
	Flex	.00	.00	.00	.30	.38	.56	.58	.29	.57	.35	.32	.46	.37	0.00
	Rigid	.00	.00	.00	.40	.38	.93	.74	.36	.97	.65	.37	.59	.64	0.00
	GVW	2.0	4.0	4.4	25.7	18.7	34.2	34.5	28.1	52.4	52.9	30.8	53.9	59.7	0.0
S	Num	3	1,222	852	2	21	20	2	12	129	92	1	2	18	0
	Flex	.00	.00	.00	.20	.36	.43	.50	.19	.74	.48	.19	.26	.72	0.00
	Rigid	.00	.00	.00	.24	.36	.60	.67	.22	1.27	1.20	.18	.29	1.25	0.00
	GVW	2.5	3.8	4.6	23.1	18.8	32.2	36.2	24.4	55.2	80.7	27.4	39.4	76.0	0.0
N Lane1	Num	6	1,253	867	1	24	16	2	19	125	82	2	2	17	0
	Flex	.00	.00	.00	.30	.38	.56	.58	.29	.57	.35	.32	.46	.37	0.00
	Rigid	.00	.00	.00	.40	.38	.93	.74	.36	.97	.65	.37	.59	.64	0.00
	GVW	2.0	4.0	4.4	25.7	18.7	34.2	34.5	28.1	52.4	52.9	30.8	53.9	59.7	0.0
S Lane1	Num	3	1,222	852	2	21	20	2	12	129	92	1	2	18	0
	Flex	.00	.00	.00	.20	.36	.43	.50	.19	.74	.48	.19	.26	.72	0.00
	Rigid	.00	.00	.00	.24	.36	.60	.67	.22	1.27	1.20	.18	.29	1.25	0.00
	GVW	2.5	3.8	4.6	23.1	18.8	32.2	36.2	24.4	55.2	80.7	27.4	39.4	76.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9