

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	8	2,080	1,723	1	41	48	3	39	219	165	2	4	33	0
	Flex	.00	.00	.00	.17	.45	.58	.58	.21	.71	.47	.17	.44	.61	0.00
	Rigid	.00	.00	.00	.16	.47	.98	.88	.30	1.19	1.06	.32	.54	1.07	0.00
	GVW	2.5	3.8	4.4	17.4	19.2	31.6	36.5	26.3	52.3	67.4	40.0	42.8	66.8	0.0
N	Num	6	1,040	863	1	21	21	3	22	108	79	1	2	17	0
	Flex	.00	.00	.00	.22	.52	.80	.49	.25	.67	.47	.16	.50	.65	0.00
	Rigid	.00	.00	.00	.21	.54	1.41	.77	.36	1.13	.94	.35	.61	1.15	0.00
	GVW	2.5	3.8	4.3	20.7	19.9	33.9	35.9	27.3	51.2	55.4	41.9	46.2	65.6	0.0
S	Num	2	1,040	860	1	20	26	2	17	111	86	1	2	17	0
	Flex	.00	.00	.00	.14	.37	.35	.60	.16	.76	.49	.22	.36	.60	0.00
	Rigid	.00	.00	.00	.13	.37	.50	.83	.23	1.26	1.21	.22	.44	1.03	0.00
	GVW	2.1	3.7	4.5	15.6	18.3	29.5	32.9	24.8	53.4	78.4	31.3	40.7	68.2	0.0
N Lane1	Num	6	1,040	863	1	21	21	3	22	108	79	1	2	17	0
	Flex	.00	.00	.00	.22	.52	.80	.49	.25	.67	.47	.16	.50	.65	0.00
	Rigid	.00	.00	.00	.21	.54	1.41	.77	.36	1.13	.94	.35	.61	1.15	0.00
	GVW	2.5	3.8	4.3	20.7	19.9	33.9	35.9	27.3	51.2	55.4	41.9	46.2	65.6	0.0
S Lane1	Num	2	1,040	860	1	20	26	2	17	111	86	1	2	17	0
	Flex	.00	.00	.00	.14	.37	.35	.60	.16	.76	.49	.22	.36	.60	0.00
	Rigid	.00	.00	.00	.13	.37	.50	.83	.23	1.26	1.21	.22	.44	1.03	0.00
	GVW	2.1	3.7	4.5	15.6	18.3	29.5	32.9	24.8	53.4	78.4	31.3	40.7	68.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9