

Idaho Transportation Department

Monthly WIM Distribution for May-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	12	2,824	2,193	2	53	75	6	53	230	183	2	5	33	0
	Flex	.00	.00	.00	.34	.50	.48	.49	.22	.69	.50	.25	.43	.70	0.00
	Rigid	.00	.00	.00	.36	.52	.76	.78	.37	1.20	1.12	.42	.55	1.25	0.00
	GVW	2.3	3.7	4.5	22.3	19.1	31.1	38.4	26.0	51.9	66.6	35.2	47.6	69.2	0.0
N	Num	7	1,386	1,097	1	27	36	3	30	110	87	2	2	17	0
	Flex	.00	.00	.00	.36	.51	.61	.52	.25	.73	.53	.29	.54	.70	0.00
	Rigid	.00	.00	.00	.39	.53	1.03	.78	.40	1.30	1.03	.49	.73	1.26	0.00
	GVW	2.3	3.7	4.3	23.9	18.7	33.0	37.8	26.6	52.6	55.3	37.7	54.8	66.7	0.0
S	Num	7	1,438	1,096	3	26	39	4	23	120	96	1	3	16	0
	Flex	.00	.00	.00	.36	.49	.36	.47	.19	.66	.49	.15	.23	.65	0.00
	Rigid	.00	.00	.00	.37	.50	.51	.78	.32	1.11	1.19	.18	.27	1.13	0.00
	GVW	2.2	3.8	4.5	19.9	19.4	30.0	39.7	25.0	51.1	76.3	28.1	39.2	69.2	0.0
N Lane1	Num	7	1,386	1,097	1	27	36	3	30	110	87	2	2	17	0
	Flex	.00	.00	.00	.36	.51	.61	.52	.25	.73	.53	.29	.54	.70	0.00
	Rigid	.00	.00	.00	.39	.53	1.03	.78	.40	1.30	1.03	.49	.73	1.26	0.00
	GVW	2.3	3.7	4.3	23.9	18.7	33.0	37.8	26.6	52.6	55.3	37.7	54.8	66.7	0.0
S Lane1	Num	7	1,438	1,096	3	26	39	4	23	120	96	1	3	16	0
	Flex	.00	.00	.00	.36	.49	.36	.47	.19	.66	.49	.15	.23	.65	0.00
	Rigid	.00	.00	.00	.37	.50	.51	.78	.32	1.11	1.19	.18	.27	1.13	0.00
	GVW	2.2	3.8	4.5	19.9	19.4	30.0	39.7	25.0	51.1	76.3	28.1	39.2	69.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9