

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	37	3,173	2,408	2	60	105	9	67	250	197	3	5	37	0
	Flex	.00	.00	.00	.40	.54	.56	.50	.29	.64	.52	.20	.65	.68	0.00
	Rigid	.00	.00	.00	.47	.56	.87	.91	.48	1.11	1.17	.42	.73	1.19	0.00
	GVW	2.5	3.7	4.5	23.9	19.4	31.7	40.2	29.4	51.6	68.2	37.7	50.4	67.3	0.0
N	Num	19	1,553	1,209	2	29	55	5	35	123	93	2	3	19	0
	Flex	.00	.00	.00	.66	.41	.79	.90	.30	.69	.47	.25	.73	.63	0.00
	Rigid	.00	.00	.00	.75	.42	1.25	1.28	.47	1.19	.94	.57	.85	1.16	0.00
	GVW	2.6	3.6	4.4	25.4	18.3	33.6	35.4	28.4	52.7	56.2	41.9	54.2	67.0	0.0
S	Num	18	1,620	1,199	1	30	50	6	32	127	104	2	3	19	0
	Flex	.00	.00	.00	.38	.67	.39	.42	.28	.59	.56	.15	.26	.73	0.00
	Rigid	.00	.00	.00	.44	.69	.59	.98	.50	1.02	1.33	.25	.30	1.23	0.00
	GVW	2.5	3.8	4.6	25.7	20.4	30.8	47.8	30.6	50.3	77.5	34.2	41.7	68.1	0.0
N Lane1	Num	19	1,553	1,209	2	29	55	5	35	123	93	2	3	19	0
	Flex	.00	.00	.00	.66	.41	.79	.90	.30	.69	.47	.25	.73	.63	0.00
	Rigid	.00	.00	.00	.75	.42	1.25	1.28	.47	1.19	.94	.57	.85	1.16	0.00
	GVW	2.6	3.6	4.4	25.4	18.3	33.6	35.4	28.4	52.7	56.2	41.9	54.2	67.0	0.0
S Lane1	Num	18	1,620	1,199	1	30	50	6	32	127	104	2	3	19	0
	Flex	.00	.00	.00	.38	.67	.39	.42	.28	.59	.56	.15	.26	.73	0.00
	Rigid	.00	.00	.00	.44	.69	.59	.98	.50	1.02	1.33	.25	.30	1.23	0.00
	GVW	2.5	3.8	4.6	25.7	20.4	30.8	47.8	30.6	50.3	77.5	34.2	41.7	68.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9