

Idaho Transportation Department

Monthly WIM Distribution for Jul-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3,000	3,576	2,663	2	63	101	11	94	254	166	4	5	40	0
	Flex	.03	.00	.00	.97	.62	.55	.57	.31	.75	.57	.64	.53	.72	0.00
	Rigid	.05	.00	.00	1.22	.65	.89	.83	.49	1.30	1.26	.96	.71	1.32	0.00
	GVW	5.3	3.9	4.4	30.4	19.8	32.2	36.1	26.5	53.1	68.8	41.4	50.4	69.9	0.0
N	Num	1,643	1,753	1,334	1	34	41	7	57	124	83	3	2	20	0
	Flex	.04	.00	.00	1.23	.80	.75	.50	.33	.81	.54	.53	.80	.57	0.00
	Rigid	.06	.00	.00	1.56	.85	1.29	.76	.58	1.40	1.08	.93	1.12	1.04	0.00
	GVW	5.3	3.8	4.3	36.2	20.5	33.9	36.6	28.9	54.3	58.4	45.2	57.5	62.3	0.0
S	Num	1,543	1,823	1,329	2	29	60	4	36	131	84	2	3	20	0
	Flex	.03	.00	.00	.56	.41	.39	.67	.27	.69	.60	.53	.28	.88	0.00
	Rigid	.05	.00	.00	.78	.42	.58	.90	.35	1.21	1.43	.59	.33	1.57	0.00
	GVW	5.4	4.0	4.5	27.1	19.0	31.2	34.7	22.1	51.8	77.7	30.1	43.7	76.5	0.0
N Lane1	Num	1,643	1,753	1,334	1	34	41	7	57	124	83	3	2	20	0
	Flex	.04	.00	.00	1.23	.80	.75	.50	.33	.81	.54	.53	.80	.57	0.00
	Rigid	.06	.00	.00	1.56	.85	1.29	.76	.58	1.40	1.08	.93	1.12	1.04	0.00
	GVW	5.3	3.8	4.3	36.2	20.5	33.9	36.6	28.9	54.3	58.4	45.2	57.5	62.3	0.0
S Lane1	Num	1,543	1,823	1,329	2	29	60	4	36	131	84	2	3	20	0
	Flex	.03	.00	.00	.56	.41	.39	.67	.27	.69	.60	.53	.28	.88	0.00
	Rigid	.05	.00	.00	.78	.42	.58	.90	.35	1.21	1.43	.59	.33	1.57	0.00
	GVW	5.4	4.0	4.5	27.1	19.0	31.2	34.7	22.1	51.8	77.7	30.1	43.7	76.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2020

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9