

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2021

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	46	3,724	2,888	2	79	129	16	95	283	165	3	4	45	0
	Flex	.00	.00	.00	.37	.56	.57	.52	.34	.76	.58	.27	.90	.79	0.00
	Rigid	.00	.00	.00	.56	.58	.94	.91	.56	1.32	1.30	.38	1.27	1.45	0.00
	GVW	2.4	3.8	4.4	20.8	19.4	32.6	42.1	28.7	54.0	70.5	34.5	52.6	73.1	0.0
N	Num	37	1,796	1,435	1	42	55	9	56	139	80	2	3	24	0
	Flex	.00	.00	.00	.40	.68	.77	.72	.37	.82	.60	.28	.89	.85	0.00
	Rigid	.00	.00	.00	.51	.72	1.33	1.12	.64	1.43	1.22	.39	1.30	1.59	0.00
	GVW	2.5	3.7	4.3	21.7	19.9	34.3	41.4	30.4	54.8	61.9	33.4	57.5	73.5	0.0
S	Num	15	1,928	1,453	2	37	75	8	39	144	85	2	2	20	0
	Flex	.00	.00	.00	.36	.43	.39	.45	.28	.70	.56	.26	.41	.72	0.00
	Rigid	.00	.00	.00	.61	.44	.58	.89	.43	1.22	1.37	.33	.48	1.24	0.00
	GVW	2.4	3.9	4.5	21.9	19.0	30.9	44.5	25.8	53.1	78.4	33.2	40.5	71.3	0.0
N Lane1	Num	37	1,796	1,435	1	42	55	9	56	139	80	2	3	24	0
	Flex	.00	.00	.00	.40	.68	.77	.72	.37	.82	.60	.28	.89	.85	0.00
	Rigid	.00	.00	.00	.51	.72	1.33	1.12	.64	1.43	1.22	.39	1.30	1.59	0.00
	GVW	2.5	3.7	4.3	21.7	19.9	34.3	41.4	30.4	54.8	61.9	33.4	57.5	73.5	0.0
S Lane1	Num	15	1,928	1,453	2	37	75	8	39	144	85	2	2	20	0
	Flex	.00	.00	.00	.36	.43	.39	.45	.28	.70	.56	.26	.41	.72	0.00
	Rigid	.00	.00	.00	.61	.44	.58	.89	.43	1.22	1.37	.33	.48	1.24	0.00
	GVW	2.4	3.9	4.5	21.9	19.0	30.9	44.5	25.8	53.1	78.4	33.2	40.5	71.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2021

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp: 9

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9