

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2021

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	38	4,059	3,004	2	79	117	15	102	279	155	4	5	39	0
	Flex	.00	.00	.00	.99	.45	.58	.52	.38	.79	.60	.27	.63	.86	0.00
	Rigid	.00	.00	.00	1.28	.46	.96	.86	.57	1.37	1.32	.35	.93	1.44	0.00
	GVW	2.4	4.0	4.3	27.6	19.0	33.0	39.6	27.2	54.1	70.6	31.0	52.5	72.1	0.0
N	Num	31	2,017	1,504	2	41	49	9	58	138	78	2	3	19	0
	Flex	.00	.00	.00	1.84	.47	.85	.50	.37	.76	.57	.18	.91	.72	0.00
	Rigid	.00	.00	.00	2.28	.48	1.48	.76	.59	1.34	1.12	.24	1.48	1.24	0.00
	GVW	2.4	3.9	4.3	32.2	18.8	35.6	38.3	28.1	54.4	62.6	28.7	59.0	67.3	0.0
S	Num	11	2,041	1,500	1	38	68	6	44	141	77	2	2	20	0
	Flex	.00	.00	.00	.45	.43	.38	.59	.40	.81	.63	.35	.41	.98	0.00
	Rigid	.00	.00	.00	.65	.43	.56	1.01	.53	1.41	1.50	.43	.48	1.62	0.00
	GVW	2.2	4.0	4.3	19.3	19.0	31.0	41.8	25.6	53.7	77.7	32.9	46.8	76.2	0.0
N Lane1	Num	31	2,017	1,504	2	41	49	9	58	138	78	2	3	19	0
	Flex	.00	.00	.00	1.84	.47	.85	.50	.37	.76	.57	.18	.91	.72	0.00
	Rigid	.00	.00	.00	2.28	.48	1.48	.76	.59	1.34	1.12	.24	1.48	1.24	0.00
	GVW	2.4	3.9	4.3	32.2	18.8	35.6	38.3	28.1	54.4	62.6	28.7	59.0	67.3	0.0
S Lane1	Num	11	2,041	1,500	1	38	68	6	44	141	77	2	2	20	0
	Flex	.00	.00	.00	.45	.43	.38	.59	.40	.81	.63	.35	.41	.98	0.00
	Rigid	.00	.00	.00	.65	.43	.56	1.01	.53	1.41	1.50	.43	.48	1.62	0.00
	GVW	2.2	4.0	4.3	19.3	19.0	31.0	41.8	25.6	53.7	77.7	32.9	46.8	76.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2021

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp: 9

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9