

Idaho Transportation Department

Monthly WIM Distribution for Aug-2021

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	34	3,888	2,879	2	78	120	15	83	291	185	3	5	45	0
	Flex	.00	.00	.00	.43	.45	.53	.45	.33	.67	.53	.18	.52	.76	0.00
	Rigid	.00	.00	.00	.55	.46	.85	.75	.49	1.15	1.16	.22	.63	1.34	0.00
	GVW	2.3	3.8	4.4	29.2	18.5	32.1	37.7	27.3	52.3	68.7	32.0	48.4	73.2	0.0
N	Num	26	1,918	1,437	2	41	49	8	48	148	90	2	3	24	0
	Flex	.00	.00	.00	.49	.52	.75	.44	.35	.69	.52	.18	.69	.64	0.00
	Rigid	.00	.00	.00	.62	.54	1.29	.69	.54	1.21	1.08	.22	.84	1.17	0.00
	GVW	2.2	3.7	4.3	31.5	18.7	34.7	35.9	28.9	53.0	62.0	31.5	54.2	69.3	0.0
S	Num	8	1,970	1,442	1	37	70	7	34	143	95	2	3	21	0
	Flex	.00	.00	.00	.34	.37	.37	.45	.30	.65	.53	.14	.49	.86	0.00
	Rigid	.00	.00	.00	.43	.37	.53	.81	.41	1.12	1.23	.16	.60	1.48	0.00
	GVW	2.3	3.9	4.5	24.7	18.3	30.2	39.6	24.7	51.5	74.4	29.2	45.9	75.5	0.0
N Lane1	Num	26	1,918	1,437	2	41	49	8	48	148	90	2	3	24	0
	Flex	.00	.00	.00	.49	.52	.75	.44	.35	.69	.52	.18	.69	.64	0.00
	Rigid	.00	.00	.00	.62	.54	1.29	.69	.54	1.21	1.08	.22	.84	1.17	0.00
	GVW	2.2	3.7	4.3	31.5	18.7	34.7	35.9	28.9	53.0	62.0	31.5	54.2	69.3	0.0
S Lane1	Num	8	1,970	1,442	1	37	70	7	34	143	95	2	3	21	0
	Flex	.00	.00	.00	.34	.37	.37	.45	.30	.65	.53	.14	.49	.86	0.00
	Rigid	.00	.00	.00	.43	.37	.53	.81	.41	1.12	1.23	.16	.60	1.48	0.00
	GVW	2.3	3.9	4.5	24.7	18.3	30.2	39.6	24.7	51.5	74.4	29.2	45.9	75.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2021

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9