

Idaho Transportation Department

Monthly WIM Distribution for Oct-2021

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	35	3,428	2,627	2	73	127	15	63	277	177	3	6	41	0
	Flex	.00	.00	.00	.47	.37	.40	.29	.24	.59	.45	.18	.31	.56	0.00
	Rigid	.00	.00	.00	.63	.37	.64	.52	.41	1.00	1.02	.23	.40	1.05	0.00
	GVW	2.7	3.9	4.5	25.7	18.5	30.4	35.5	29.4	51.5	68.6	31.8	47.0	70.2	0.0
N	Num	30	1,704	1,307	1	37	53	10	38	134	84	2	3	22	0
	Flex	.00	.00	.00	.32	.35	.58	.25	.25	.56	.41	.14	.36	.51	0.00
	Rigid	.00	.00	.00	.37	.35	.98	.48	.46	.94	.87	.17	.49	.99	0.00
	GVW	2.6	3.9	4.4	22.1	18.3	33.7	35.6	31.0	51.0	60.7	28.2	52.8	68.6	0.0
S	Num	9	1,723	1,321	1	36	74	5	25	142	92	2	3	20	0
	Flex	.00	.00	.00	.49	.39	.27	.32	.22	.62	.48	.19	.29	.65	0.00
	Rigid	.00	.00	.00	.74	.39	.40	.52	.34	1.05	1.13	.29	.34	1.14	0.00
	GVW	3.1	3.9	4.6	27.4	18.7	28.3	35.3	26.5	51.9	75.1	36.3	42.3	71.6	0.0
N Lane1	Num	30	1,704	1,307	1	37	53	10	38	134	84	2	3	22	0
	Flex	.00	.00	.00	.32	.35	.58	.25	.25	.56	.41	.14	.36	.51	0.00
	Rigid	.00	.00	.00	.37	.35	.98	.48	.46	.94	.87	.17	.49	.99	0.00
	GVW	2.6	3.9	4.4	22.1	18.3	33.7	35.6	31.0	51.0	60.7	28.2	52.8	68.6	0.0
S Lane1	Num	9	1,723	1,321	1	36	74	5	25	142	92	2	3	20	0
	Flex	.00	.00	.00	.49	.39	.27	.32	.22	.62	.48	.19	.29	.65	0.00
	Rigid	.00	.00	.00	.74	.39	.40	.52	.34	1.05	1.13	.29	.34	1.14	0.00
	GVW	3.1	3.9	4.6	27.4	18.7	28.3	35.3	26.5	51.9	75.1	36.3	42.3	71.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2021

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9