

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2021

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	36	3,100	2,432	2	60	101	9	51	299	167	4	6	33	0
	Flex	.00	.00	.00	.30	.37	.40	.20	.22	.53	.42	.34	.37	.55	0.00
	Rigid	.00	.00	.00	.44	.37	.62	.40	.39	.91	.93	.51	.49	.99	0.00
	GVW	2.4	4.0	4.5	21.7	18.5	31.0	33.9	30.9	52.5	67.9	38.6	49.8	71.1	0.0
N	Num	31	1,546	1,210	1	31	42	7	29	144	79	3	3	16	0
	Flex	.00	.00	.00	.21	.40	.57	.22	.24	.49	.40	.42	.48	.47	0.00
	Rigid	.00	.00	.00	.23	.40	.91	.49	.40	.85	.81	.70	.62	.87	0.00
	GVW	2.6	4.1	4.5	21.2	18.7	34.2	38.2	31.6	52.3	61.9	44.2	56.7	66.6	0.0
S	Num	11	1,554	1,223	1	29	59	3	21	155	88	2	3	17	0
	Flex	.00	.00	.00	.37	.34	.30	.17	.21	.56	.45	.28	.22	.62	0.00
	Rigid	.00	.00	.00	.58	.34	.43	.27	.35	.97	1.04	.31	.29	1.10	0.00
	GVW	2.4	4.0	4.6	22.0	18.2	29.0	27.4	29.9	52.5	73.6	32.4	40.4	74.7	0.0
N Lane1	Num	31	1,546	1,210	1	31	42	7	29	144	79	3	3	16	0
	Flex	.00	.00	.00	.21	.40	.57	.22	.24	.49	.40	.42	.48	.47	0.00
	Rigid	.00	.00	.00	.23	.40	.91	.49	.40	.85	.81	.70	.62	.87	0.00
	GVW	2.6	4.1	4.5	21.2	18.7	34.2	38.2	31.6	52.3	61.9	44.2	56.7	66.6	0.0
S Lane1	Num	11	1,554	1,223	1	29	59	3	21	155	88	2	3	17	0
	Flex	.00	.00	.00	.37	.34	.30	.17	.21	.56	.45	.28	.22	.62	0.00
	Rigid	.00	.00	.00	.58	.34	.43	.27	.35	.97	1.04	.31	.29	1.10	0.00
	GVW	2.4	4.0	4.6	22.0	18.2	29.0	27.4	29.9	52.5	73.6	32.4	40.4	74.7	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2021

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp: 9

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9