

Idaho Transportation Department

Monthly WIM Distribution for Dec-2021

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	33	2,717	2,096	2	55	91	7	42	320	140	4	5	26	0
	Flex	.00	.00	.00	.21	.38	.57	.20	.29	.60	.50	.46	.46	.61	0.00
	Rigid	.00	.00	.00	.26	.38	.90	.42	.49	1.05	1.08	.71	.53	1.06	0.00
	GVW	2.5	4.1	4.4	20.1	18.7	32.6	33.5	33.6	53.9	67.8	36.4	50.6	68.7	0.0
N	Num	22	1,364	1,050	1	28	42	6	23	162	65	2	3	12	0
	Flex	.00	.00	.00	.24	.37	.64	.27	.27	.51	.45	.53	.54	.47	0.00
	Rigid	.00	.00	.00	.27	.37	1.03	.55	.45	.90	.90	.94	.64	.82	0.00
	GVW	2.5	4.2	4.4	21.6	18.8	34.1	41.9	33.4	53.1	60.9	35.0	55.8	66.2	0.0
S	Num	14	1,353	1,046	1	27	49	3	20	158	75	2	3	14	0
	Flex	.00	.00	.00	.26	.40	.49	.20	.30	.67	.55	.43	.38	.74	0.00
	Rigid	.00	.00	.00	.29	.40	.73	.48	.51	1.18	1.25	.56	.42	1.31	0.00
	GVW	2.4	4.1	4.4	17.6	18.7	31.7	34.2	33.4	54.2	73.8	38.3	45.9	71.8	0.0
N Lane1	Num	22	1,364	1,050	1	28	42	6	23	162	65	2	3	12	0
	Flex	.00	.00	.00	.24	.37	.64	.27	.27	.51	.45	.53	.54	.47	0.00
	Rigid	.00	.00	.00	.27	.37	1.03	.55	.45	.90	.90	.94	.64	.82	0.00
	GVW	2.5	4.2	4.4	21.6	18.8	34.1	41.9	33.4	53.1	60.9	35.0	55.8	66.2	0.0
S Lane1	Num	14	1,353	1,046	1	27	49	3	20	158	75	2	3	14	0
	Flex	.00	.00	.00	.26	.40	.49	.20	.30	.67	.55	.43	.38	.74	0.00
	Rigid	.00	.00	.00	.29	.40	.73	.48	.51	1.18	1.25	.56	.42	1.31	0.00
	GVW	2.4	4.1	4.4	17.6	18.7	31.7	34.2	33.4	54.2	73.8	38.3	45.9	71.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2021

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9