

Idaho Transportation Department

Monthly WIM Distribution for Feb-2022

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	57	2,883	2,076	2	56	97	10	51	271	149	2	6	29	0
	Flex	.00	.00	.00	.36	.40	.37	.44	.24	.60	.47	.26	.39	.66	0.00
	Rigid	.00	.00	.00	.49	.40	.56	.84	.47	1.05	1.02	.39	.45	1.10	0.00
	GVW	2.6	4.0	4.5	27.0	19.0	30.8	45.1	35.5	54.3	69.3	35.4	49.0	72.2	0.0
N	Num	33	1,442	1,039	1	28	50	6	27	137	70	2	3	13	0
	Flex	.00	.00	.00	.27	.37	.41	.43	.21	.57	.41	.33	.45	.49	0.00
	Rigid	.00	.00	.00	.33	.37	.66	.78	.43	.99	.81	.46	.53	.84	0.00
	GVW	2.6	4.1	4.4	22.5	18.7	31.8	44.2	34.2	54.7	60.3	36.4	51.7	66.4	0.0
S	Num	24	1,442	1,037	1	28	47	5	24	134	79	1	3	16	0
	Flex	.00	.00	.00	.37	.42	.31	.35	.26	.64	.53	.22	.28	.80	0.00
	Rigid	.00	.00	.00	.49	.42	.45	.87	.49	1.10	1.21	.31	.31	1.31	0.00
	GVW	2.6	4.0	4.5	24.2	19.2	29.6	45.3	36.2	53.7	77.3	35.7	44.5	75.5	0.0
N Lane1	Num	33	1,442	1,039	1	28	50	6	27	137	70	2	3	13	0
	Flex	.00	.00	.00	.27	.37	.41	.43	.21	.57	.41	.33	.45	.49	0.00
	Rigid	.00	.00	.00	.33	.37	.66	.78	.43	.99	.81	.46	.53	.84	0.00
	GVW	2.6	4.1	4.4	22.5	18.7	31.8	44.2	34.2	54.7	60.3	36.4	51.7	66.4	0.0
S Lane1	Num	24	1,442	1,037	1	28	47	5	24	134	79	1	3	16	0
	Flex	.00	.00	.00	.37	.42	.31	.35	.26	.64	.53	.22	.28	.80	0.00
	Rigid	.00	.00	.00	.49	.42	.45	.87	.49	1.10	1.21	.31	.31	1.31	0.00
	GVW	2.6	4.0	4.5	24.2	19.2	29.6	45.3	36.2	53.7	77.3	35.7	44.5	75.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2022

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9