

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	38	4,036	2,839	3	85	126	16	105	273	152	4	7	45	0
	Flex	.00	.00	.00	.84	.54	.58	.81	.44	.81	.60	.29	1.13	.81	0.00
	Rigid	.00	.00	.00	1.29	.56	.96	1.24	.65	1.43	1.31	.45	1.38	1.44	0.00
	GVW	2.6	3.9	4.4	33.5	18.8	31.4	39.5	27.5	53.8	69.6	36.0	54.1	70.3	0.0
N	Num	36	1,860	1,367	2	44	51	12	59	136	77	2	3	24	0
	Flex	.00	.00	.00	1.12	.62	.91	.88	.54	.97	.63	.32	1.90	.78	0.00
	Rigid	.00	.00	.00	1.79	.67	1.60	1.46	.81	1.75	1.29	.55	2.38	1.36	0.00
	GVW	2.5	4.0	4.3	38.1	18.5	35.4	41.4	29.6	55.7	64.1	38.3	58.5	64.6	0.0
S	Num	8	2,177	1,472	2	41	75	5	47	138	75	2	4	21	0
	Flex	.00	.00	.00	.63	.44	.31	.65	.31	.69	.56	.28	1.12	.82	0.00
	Rigid	.00	.00	.00	.89	.45	.43	.85	.43	1.18	1.31	.30	1.30	1.50	0.00
	GVW	2.6	3.9	4.5	29.2	19.2	28.3	36.0	24.6	51.6	74.3	29.9	56.2	75.7	0.0
N Lane1	Num	36	1,860	1,367	2	44	51	12	59	136	77	2	3	24	0
	Flex	.00	.00	.00	1.12	.62	.91	.88	.54	.97	.63	.32	1.90	.78	0.00
	Rigid	.00	.00	.00	1.79	.67	1.60	1.46	.81	1.75	1.29	.55	2.38	1.36	0.00
	GVW	2.5	4.0	4.3	38.1	18.5	35.4	41.4	29.6	55.7	64.1	38.3	58.5	64.6	0.0
S Lane1	Num	8	2,177	1,472	2	41	75	5	47	138	75	2	4	21	0
	Flex	.00	.00	.00	.63	.44	.31	.65	.31	.69	.56	.28	1.12	.82	0.00
	Rigid	.00	.00	.00	.89	.45	.43	.85	.43	1.18	1.31	.30	1.30	1.50	0.00
	GVW	2.6	3.9	4.5	29.2	19.2	28.3	36.0	24.6	51.6	74.3	29.9	56.2	75.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9