

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2022

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	4,085	2,598	4	106	113	12	83	286	158	0	12	47	0
	Flex	.03	.00	.00	.78	.60	.43	.53	.23	1.01	.80	0.00	1.49	.97	0.00
	Rigid	.06	.00	.00	1.04	.62	.73	1.11	.27	1.94	2.00	0.00	2.18	1.88	0.00
	GVW	11.0	2.7	4.7	30.7	20.5	31.2	53.3	24.0	59.0	76.2	0.0	66.5	78.7	0.0
N	Num	2	2,041	1,338	2	55	68	3	43	140	74	0	5	25	0
	Flex	.01	.00	.00	.66	.49	.23	.58	.20	.78	.66	0.00	.53	.77	0.00
	Rigid	.03	.00	.00	.87	.50	.34	1.36	.23	1.46	1.71	0.00	.76	1.50	0.00
	GVW	4.5	2.5	4.3	33.7	19.5	27.1	59.0	23.1	54.7	76.9	0.0	51.2	74.7	0.0
S	Num	8	2,044	1,260	2	50	45	12	40	146	83	0	7	23	0
	Flex	.03	.00	.01	1.16	.72	.62	.53	.27	1.25	.94	0.00	1.97	1.19	0.00
	Rigid	.07	.00	.01	1.65	.76	1.12	1.20	.32	2.45	2.29	0.00	2.93	2.32	0.00
	GVW	12.3	2.9	5.1	31.2	21.7	35.2	54.8	24.9	63.0	75.2	0.0	75.2	83.3	0.0
N Lane1	Num	2	2,041	1,338	2	55	68	3	43	140	74	0	5	25	0
	Flex	.01	.00	.00	.66	.49	.23	.58	.20	.78	.66	0.00	.53	.77	0.00
	Rigid	.03	.00	.00	.87	.50	.34	1.36	.23	1.46	1.71	0.00	.76	1.50	0.00
	GVW	4.5	2.5	4.3	33.7	19.5	27.1	59.0	23.1	54.7	76.9	0.0	51.2	74.7	0.0
S Lane1	Num	8	2,044	1,260	2	50	45	12	40	146	83	0	7	23	0
	Flex	.03	.00	.01	1.16	.72	.62	.53	.27	1.25	.94	0.00	1.97	1.19	0.00
	Rigid	.07	.00	.01	1.65	.76	1.12	1.20	.32	2.45	2.29	0.00	2.93	2.32	0.00
	GVW	12.3	2.9	5.1	31.2	21.7	35.2	54.8	24.9	63.0	75.2	0.0	75.2	83.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2022

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 6  
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9