

Idaho Transportation Department

Monthly WIM Distribution for Nov-2022

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	14	2,903	2,013	3	63	104	6	43	227	134	3	11	25	0
	Flex	.02	.00	.00	.52	.38	.34	.51	.26	.93	.71	1.55	1.23	.99	0.00
	Rigid	.04	.00	.00	.77	.37	.59	.97	.32	1.78	1.79	2.26	1.73	1.93	0.00
	GVW	11.8	2.8	4.5	29.7	20.3	32.6	54.0	27.8	63.6	82.2	69.0	73.4	87.9	0.0
N	Num	11	1,434	960	2	28	59	4	21	107	66	2	5	11	0
	Flex	.02	.00	.00	.56	.44	.38	.41	.26	.88	.66	1.77	1.58	.85	0.00
	Rigid	.03	.00	.00	.81	.43	.69	.77	.32	1.66	1.56	2.48	2.11	1.49	0.00
	GVW	12.1	3.0	4.7	30.6	21.1	33.9	49.3	27.6	63.1	74.4	72.2	78.8	78.0	0.0
S	Num	3	1,468	1,053	2	35	45	3	22	120	68	2	6	14	0
	Flex	.03	.00	.00	.53	.34	.28	.86	.26	.96	.75	.41	.96	1.06	0.00
	Rigid	.05	.00	.00	.80	.33	.45	1.40	.32	1.83	1.97	.38	1.43	2.18	0.00
	GVW	9.5	2.5	4.3	30.6	19.9	30.8	64.0	28.0	63.4	88.9	46.9	68.9	93.9	0.0
N Lane1	Num	11	1,434	960	2	28	59	4	21	107	66	2	5	11	0
	Flex	.02	.00	.00	.56	.44	.38	.41	.26	.88	.66	1.77	1.58	.85	0.00
	Rigid	.03	.00	.00	.81	.43	.69	.77	.32	1.66	1.56	2.48	2.11	1.49	0.00
	GVW	12.1	3.0	4.7	30.6	21.1	33.9	49.3	27.6	63.1	74.4	72.2	78.8	78.0	0.0
S Lane1	Num	3	1,468	1,053	2	35	45	3	22	120	68	2	6	14	0
	Flex	.03	.00	.00	.53	.34	.28	.86	.26	.96	.75	.41	.96	1.06	0.00
	Rigid	.05	.00	.00	.80	.33	.45	1.40	.32	1.83	1.97	.38	1.43	2.18	0.00
	GVW	9.5	2.5	4.3	30.6	19.9	30.8	64.0	28.0	63.4	88.9	46.9	68.9	93.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2022

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9