

Idaho Transportation Department

Monthly WIM Distribution for Dec-2022

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	2,360	1,622	3	54	90	5	27	184	114	1	10	15	0
	Flex	.02	.00	.00	.43	.41	.33	.71	.39	.97	.72	1.06	1.51	.99	0.00
	Rigid	.04	.00	.00	.53	.40	.59	1.38	.48	1.86	1.80	1.18	2.04	1.95	0.00
	GVW	12.0	3.0	4.6	23.2	20.1	32.7	60.9	32.0	64.3	81.7	43.1	75.3	87.4	0.0
N	Num	13	1,207	807	2	26	58	4	15	88	58	1	5	7	0
	Flex	.02	.00	.00	.50	.45	.38	.75	.40	.99	.67	1.99	1.65	.86	0.00
	Rigid	.03	.00	.00	.62	.44	.69	1.71	.49	1.89	1.58	2.13	2.23	1.54	0.00
	GVW	12.3	3.2	4.8	26.4	20.9	34.4	67.5	31.8	65.0	75.1	53.6	78.3	79.3	0.0
S	Num	3	1,192	843	2	29	33	2	14	98	58	1	5	10	0
	Flex	.07	.00	.00	.49	.38	.25	.77	.33	.93	.77	.03	1.33	.95	0.00
	Rigid	.14	.00	.00	.58	.37	.42	1.08	.41	1.79	2.03	.03	1.71	2.00	0.00
	GVW	10.5	2.7	4.3	23.2	19.6	30.3	55.2	31.4	63.0	88.9	24.5	71.9	90.7	0.0
N Lane1	Num	13	1,207	807	2	26	58	4	15	88	58	1	5	7	0
	Flex	.02	.00	.00	.50	.45	.38	.75	.40	.99	.67	1.99	1.65	.86	0.00
	Rigid	.03	.00	.00	.62	.44	.69	1.71	.49	1.89	1.58	2.13	2.23	1.54	0.00
	GVW	12.3	3.2	4.8	26.4	20.9	34.4	67.5	31.8	65.0	75.1	53.6	78.3	79.3	0.0
S Lane1	Num	3	1,192	843	2	29	33	2	14	98	58	1	5	10	0
	Flex	.07	.00	.00	.49	.38	.25	.77	.33	.93	.77	.03	1.33	.95	0.00
	Rigid	.14	.00	.00	.58	.37	.42	1.08	.41	1.79	2.03	.03	1.71	2.00	0.00
	GVW	10.5	2.7	4.3	23.2	19.6	30.3	55.2	31.4	63.0	88.9	24.5	71.9	90.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2022

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9