

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2023

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	3,140	1,935	3	67	83	6	33	248	151	1	13	23	0
	Flex	.02	.00	.00	.44	.38	.29	.51	.36	.90	.65	.41	1.36	.92	0.00
	Rigid	.03	.00	.00	.61	.37	.50	1.08	.42	1.70	1.63	.42	1.81	1.75	0.00
	GVW	11.4	2.8	4.5	26.2	19.9	32.3	57.5	30.7	63.3	80.4	41.6	73.5	84.8	0.0
N	Num	8	1,558	927	2	31	40	3	17	120	79	1	8	10	0
	Flex	.01	.00	.00	.60	.39	.34	.48	.40	.88	.60	.40	1.60	.99	0.00
	Rigid	.02	.00	.00	.84	.38	.61	1.14	.49	1.68	1.41	.37	2.16	1.84	0.00
	GVW	11.6	3.0	4.7	31.7	20.4	34.0	54.7	31.4	64.0	72.2	38.2	78.7	86.2	0.0
S	Num	1	1,582	1,008	2	36	43	3	16	128	73	1	5	14	0
	Flex	.14	.00	.00	.30	.36	.26	.60	.31	.91	.69	.41	.95	.92	0.00
	Rigid	.28	.00	.01	.42	.35	.41	1.21	.35	1.72	1.85	.46	1.15	1.77	0.00
	GVW	12.9	2.5	4.2	22.3	19.5	30.9	62.0	29.8	62.5	88.8	45.1	63.4	85.5	0.0
N Lane1	Num	8	1,558	927	2	31	40	3	17	120	79	1	8	10	0
	Flex	.01	.00	.00	.60	.39	.34	.48	.40	.88	.60	.40	1.60	.99	0.00
	Rigid	.02	.00	.00	.84	.38	.61	1.14	.49	1.68	1.41	.37	2.16	1.84	0.00
	GVW	11.6	3.0	4.7	31.7	20.4	34.0	54.7	31.4	64.0	72.2	38.2	78.7	86.2	0.0
S Lane1	Num	1	1,582	1,008	2	36	43	3	16	128	73	1	5	14	0
	Flex	.14	.00	.00	.30	.36	.26	.60	.31	.91	.69	.41	.95	.92	0.00
	Rigid	.28	.00	.01	.42	.35	.41	1.21	.35	1.72	1.85	.46	1.15	1.77	0.00
	GVW	12.9	2.5	4.2	22.3	19.5	30.9	62.0	29.8	62.5	88.8	45.1	63.4	85.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2023

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9