

Idaho Transportation Department

Monthly WIM Distribution for Jun-2023

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6	4,308	2,806	5	110	116	29	91	308	188	1	13	40	0
	Flex	.06	.00	.01	.62	.45	.46	.76	.17	.76	.65	1.83	1.40	1.00	0.00
	Rigid	.13	.00	.01	.89	.46	.76	1.26	.20	1.42	1.56	2.40	2.13	2.05	0.00
	GVW	11.1	2.8	4.8	33.4	19.5	32.1	55.4	21.6	55.4	72.1	57.1	67.9	89.1	0.0
N	Num	4	2,193	1,378	2	53	55	20	44	157	101	1	8	17	0
	Flex	.04	.00	.01	.62	.56	.58	.63	.19	.85	.73	2.01	1.74	.91	0.00
	Rigid	.09	.00	.01	.86	.58	1.01	1.08	.22	1.62	1.68	2.04	2.59	1.78	0.00
	GVW	11.5	2.9	5.1	29.3	20.3	34.6	49.9	21.6	57.2	68.6	46.8	74.0	78.9	0.0
S	Num	3	2,115	1,428	2	57	62	12	47	151	87	1	5	22	0
	Flex	.07	.00	.00	.63	.35	.31	.84	.15	.63	.57	1.73	.64	1.02	0.00
	Rigid	.17	.00	.00	.88	.35	.46	1.46	.19	1.13	1.46	2.58	1.10	2.11	0.00
	GVW	9.7	2.7	4.6	34.0	18.9	29.3	62.4	21.7	53.0	76.4	62.2	55.6	91.8	0.0
N Lane1	Num	4	2,193	1,378	2	53	55	20	44	157	101	1	8	17	0
	Flex	.04	.00	.01	.62	.56	.58	.63	.19	.85	.73	2.01	1.74	.91	0.00
	Rigid	.09	.00	.01	.86	.58	1.01	1.08	.22	1.62	1.68	2.04	2.59	1.78	0.00
	GVW	11.5	2.9	5.1	29.3	20.3	34.6	49.9	21.6	57.2	68.6	46.8	74.0	78.9	0.0
S Lane1	Num	3	2,115	1,428	2	57	62	12	47	151	87	1	5	22	0
	Flex	.07	.00	.00	.63	.35	.31	.84	.15	.63	.57	1.73	.64	1.02	0.00
	Rigid	.17	.00	.00	.88	.35	.46	1.46	.19	1.13	1.46	2.58	1.10	2.11	0.00
	GVW	9.7	2.7	4.6	34.0	18.9	29.3	62.4	21.7	53.0	76.4	62.2	55.6	91.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2023

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9