

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2023

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	5,958	2,926	8	111	100	18	99	289	233	1	10	61	0
	Flex	.06	.00	.00	.69	.57	.49	.54	.17	.90	.71	.16	2.06	1.09	0.00
	Rigid	.13	.00	.00	.94	.59	.84	1.14	.20	1.70	1.77	.16	2.89	2.22	0.00
	GVW	7.7	3.0	4.8	28.6	20.8	31.4	58.9	21.7	57.0	72.0	26.8	69.0	91.4	0.0
N	Num	7	2,390	1,461	4	56	47	10	48	153	135	1	5	19	0
	Flex	.07	.00	.00	.85	.75	.68	.51	.20	1.13	.92	.17	3.26	1.31	0.00
	Rigid	.15	.00	.00	1.17	.79	1.22	1.24	.24	2.21	2.29	.16	4.64	2.72	0.00
	GVW	10.5	3.1	5.2	29.6	21.8	34.9	57.3	22.5	61.5	76.4	21.3	80.8	89.6	0.0
S	Num	9	3,567	1,464	4	55	53	9	50	136	98	1	5	42	0
	Flex	.04	.00	.00	.40	.39	.29	.55	.14	.64	.48	.30	.58	.96	0.00
	Rigid	.08	.00	.00	.48	.39	.40	1.02	.16	1.13	1.19	.30	.76	1.89	0.00
	GVW	4.7	3.0	4.5	23.6	19.8	27.9	60.1	21.0	51.7	67.0	40.7	55.4	91.0	0.0
N Lane1	Num	7	2,390	1,461	4	56	47	10	48	153	135	1	5	19	0
	Flex	.07	.00	.00	.85	.75	.68	.51	.20	1.13	.92	.17	3.26	1.31	0.00
	Rigid	.15	.00	.00	1.17	.79	1.22	1.24	.24	2.21	2.29	.16	4.64	2.72	0.00
	GVW	10.5	3.1	5.2	29.6	21.8	34.9	57.3	22.5	61.5	76.4	21.3	80.8	89.6	0.0
S Lane1	Num	9	3,567	1,464	4	55	53	9	50	136	98	1	5	42	0
	Flex	.04	.00	.00	.40	.39	.29	.55	.14	.64	.48	.30	.58	.96	0.00
	Rigid	.08	.00	.00	.48	.39	.40	1.02	.16	1.13	1.19	.30	.76	1.89	0.00
	GVW	4.7	3.0	4.5	23.6	19.8	27.9	60.1	21.0	51.7	67.0	40.7	55.4	91.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2023

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9