



NOTES

1. PROVIDE BRASS OR BRONZE CAP AS SHOWN ON STD. DWG. I-2-A MONUMENT MARKERS & WITNESS POSTS.
2. CONSTRUCT CONCRETE COLLAR AROUND CASING AS SHOWN. USE NON-STRUCTURAL CONCRETE IN ACCORDANCE WITH SECTION 509 - NON-STRUCTURAL CONCRETE OF THE STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.
3. ANCHOR BRASS OR BRONZE CAP WITH GROUT, TYPE "D" IN ACCORDANCE WITH SECTION 705 - GROUT AND MORTAR OF THE STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.
4. MACHINE COVER AND CASING CONTACT SURFACES TO A TRUE BEARING ALL AROUND.
5. EQUIVALENT OR HEAVIER CASING DESIGNS MAY BE USED WITH PRIOR APPROVAL FROM THE ENGINEER.

ORIGINAL STORED
AT: ITD,
Headquarters
3311 West State
Boise, Idaho

ORIGINAL SIGNED BY:
RYAN D. LANCASTER
DATE ORIGINAL SIGNED:
DECEMBER 17, 2012

REVISIONS								
NO.	DATE	BY	NO.	DATE	BY	NO.	DATE	BY
1	9-93	MSM	6	6-05	MSM			
2	5-95	MSM	7	11-06	MSM			
3	1-97	MSM	8	6-07	MSM			
4	10-02	MSM	9	12-12	RDL			
5	12-04	MSM						

SCALES SHOWN
ARE FOR 11" X 17"
PRINTS ONLY

CADD FILE NAME:
i2b_1212.std

DRAWING DATE:
MARCH, 1974

**IDAHO
TRANSPORTATION
DEPARTMENT**



BOISE IDAHO

ORIGINAL SIGNED BY: LOREN THOMAS
HIGHWAYS PROGRAM OVERSIGHT ENGINEER

ORIGINAL SIGNED BY: TOM COLE
CHIEF ENGINEER

STANDARD DRAWING

**STREET MONUMENT MARKER
& INSTALLATION**

REQUIRES STD. DWG. I-2-A

English

STANDARD DRAWING NO.
I-2-B

SHEET 1 OF 1