

Idaho Transportation Department  
Percent of MADT At Continuous Count Speed Sites

Site ID: 001010 058.730

Scheme ID: 6

Location: #002 I-84 4.3 Mi. S.E. of Brdway IC (Jean's Plac

County: ADA

Axle Factor Group: 1

Growth Factor Group: 3

Seasonal Factor Group: 3

FHWA Functional Class: 1

Speed Limit: 75

| SPEED    | 1997 Traffic Year |        |        |        |        |     |     |     |     |     |        |        |      |
|----------|-------------------|--------|--------|--------|--------|-----|-----|-----|-----|-----|--------|--------|------|
|          | Jan               | Feb    | Mar    | Apr    | May    | Jun | Jul | Aug | Sep | Oct | Nov    | Dec    | Avg  |
| 0>-30    | 2.1               | 6.2    | 4.5    | 4.5    | 3.9    | .   | .   | .   | .   | .   | 0.0    | 0.0    | 3.0  |
| 30>-35   | 0.2               | 0.3    | 0.2    | 0.2    | 0.2    | .   | .   | .   | .   | .   | 0.0    | 0.0    | 0.1  |
| 35>-40   | 0.3               | 0.2    | 0.2    | 0.2    | 0.1    | .   | .   | .   | .   | .   | 0.0    | 0.0    | 0.2  |
| 40>-45   | 0.6               | 0.2    | 0.3    | 0.2    | 0.2    | .   | .   | .   | .   | .   | 0.0    | 0.0    | 0.2  |
| 45>-50   | 1.1               | 0.6    | 0.7    | 0.7    | 0.6    | .   | .   | .   | .   | .   | 0.2    | 0.2    | 0.6  |
| 50>-55   | 3.7               | 3.2    | 3.8    | 4.2    | 3.6    | .   | .   | .   | .   | .   | 2.0    | 1.6    | 3.2  |
| 55>-60   | 11.6              | 9.8    | 10.6   | 11.7   | 10.5   | .   | .   | .   | .   | .   | 9.8    | 6.7    | 10.1 |
| 60>-65   | 19.3              | 16.9   | 17.7   | 18.2   | 17.6   | .   | .   | .   | .   | .   | 20.1   | 15.8   | 17.9 |
| 65>-70   | 22.9              | 21.5   | 21.6   | 21.1   | 22.1   | .   | .   | .   | .   | .   | 26.3   | 22.9   | 22.6 |
| 70>-75   | 22.8              | 22.7   | 22.6   | 22.5   | 22.7   | .   | .   | .   | .   | .   | 24.3   | 26.9   | 23.5 |
| 75>-80   | 12.3              | 13.0   | 12.9   | 12.1   | 13.6   | .   | .   | .   | .   | .   | 13.6   | 20.3   | 14.0 |
| 80>-85   | 2.5               | 3.6    | 3.3    | 3.0    | 3.5    | .   | .   | .   | .   | .   | 3.2    | 4.7    | 3.4  |
| 85>-140  | 0.7               | 1.8    | 1.5    | 1.4    | 1.4    | .   | .   | .   | .   | .   | 0.5    | 0.8    | 1.1  |
| AVG SPD  | 66.2              | 65.4   | 65.8   | 65.5   | 66.4   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 68.4   | 70.2   | 66.8 |
| 50% SPD  | 67.4              | 67.9   | 67.8   | 67.4   | 68.0   | .   | .   | .   | .   | .   | 68.4   | 70.5   | 68.2 |
| 85% SPD  | 75.2              | 76.3   | 76.0   | 75.6   | 76.3   | .   | .   | .   | .   | .   | 75.8   | 77.7   | 76.3 |
| %EXCD 55 | 92.0              | 89.2   | 90.3   | 90.0   | 91.5   | .   | .   | .   | .   | .   | 97.7   | 98.0   | 92.7 |
| %EXCD 60 | 80.4              | 79.4   | 79.6   | 78.3   | 80.9   | .   | .   | .   | .   | .   | 87.9   | 91.4   | 82.6 |
| %EXCD 65 | 61.2              | 62.5   | 61.9   | 60.1   | 63.3   | .   | .   | .   | .   | .   | 67.8   | 75.6   | 64.6 |
| %EXCD 70 | 38.3              | 41.0   | 40.3   | 39.0   | 41.2   | .   | .   | .   | .   | .   | 41.5   | 52.6   | 42.0 |
| %EXCD 75 | 15.5              | 18.4   | 17.6   | 16.5   | 18.5   | .   | .   | .   | .   | .   | 17.3   | 25.8   | 18.5 |
| %EXCD 80 | 3.2               | 5.3    | 4.8    | 4.4    | 4.9    | .   | .   | .   | .   | .   | 3.7    | 5.5    | 4.5  |
| %EXCD 85 | 0.7               | 1.8    | 1.5    | 1.4    | 1.4    | .   | .   | .   | .   | .   | 0.5    | 0.8    | 1.1  |
|          | 13,735            | 14,863 | 17,066 | 16,966 | 17,800 | .   | .   | .   | .   | .   | 19,773 | 16,143 |      |