

Monthly WIM Distribution for 10/2011

Site Names: 00079, Downey WIM
 County: Bannock (3)
 Funct. Class: R Principal Arterial - Interstate
 Location: I-15 3.2 Mi. S of Jct SH-40

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	6	2,787	1,159	48	163	20	1	19	645	58	10	12	104	54	0
	Flex	0.00	0.00	0.00	0.83	0.23	0.41	2.30	0.39	1.07	0.76	1.22	0.78	1.27	0.43	0.00
	Rigid	0.00	0.00	0.00	0.95	0.23	0.63	4.36	0.45	1.72	1.53	1.19	0.85	1.84	0.54	0.00
	GVW	3.8	3.2	5.7	26.5	17.7	26.9	65.1	30.2	53.6	61.5	53.5	56.3	74.3	19.1	0.0
S DIR	Num	1	650	328	10	30	3	0	5	111	18	3	2	26	25	0
	Flex	0.00	0.00	0.00	0.53	0.13	0.39	0.00	0.29	0.72	0.43	0.84	0.68	0.88	0.22	0.00
	Rigid	0.00	0.00	0.00	0.63	0.15	0.53	0.00	0.40	1.14	0.83	0.80	0.77	1.32	0.26	0.00
	GVW	6.1	3.1	4.8	22.8	17.7	32.1	0.0	36.2	44.0	68.2	82.5	102.7	57.2	13.9	0.0
N DIR	Num	4	2,137	831	38	133	17	1	15	535	40	8	9	77	29	0
	Flex	0.00	0.00	0.00	0.93	0.25	0.42	2.30	0.46	1.14	0.96	1.45	0.93	1.43	0.63	0.00
	Rigid	0.00	0.00	0.00	1.05	0.25	0.66	4.37	0.52	1.83	1.95	1.42	1.02	2.07	0.81	0.00
	GVW	4.1	3.3	6.1	27.7	17.8	27.2	64.0	32.6	55.5	67.6	57.1	63.3	81.4	24.6	0.0
S 1	Num	1	249	197	9	25	3	0	4	103	17	2	2	25	17	0
	Flex	0.00	0.00	0.00	1.00	0.34	0.44	0.00	0.50	1.85	0.76	0.94	0.67	2.12	0.58	0.00
	Rigid	0.00	0.00	0.00	1.16	0.38	0.60	0.00	0.71	2.91	1.44	0.90	0.76	3.05	0.68	0.00
	GVW	12.6	7.7	12.1	55.7	45.8	49.9	0.0	57.8	115.5	121.8	96.7	100.0	144.2	37.9	0.0
S 2	Num	0	401	131	1	6	1	0	0	8	1	0	0	2	8	0
	Flex	0.00	0.00	0.00	1.94	0.15	2.91	0.00	0.29	1.37	1.05	1.37	0.00	1.39	0.18	0.00
	Rigid	0.00	0.00	0.00	2.47	0.15	3.92	0.00	0.29	2.13	2.16	1.29	0.00	2.42	0.23	0.00
	GVW	10.1	4.2	4.9	39.8	19.9	124.4	0.0	157.5	74.7	123.6	330.7	0.0	93.5	9.8	0.0
N 2	Num	1	535	170	1	5	1	0	0	12	1	0	0	2	3	0
	Flex	0.00	0.00	0.00	0.22	0.16	0.16	0.00	0.53	0.39	0.57	0.00	2.29	0.86	0.02	0.00
	Rigid	0.00	0.00	0.00	0.28	0.16	0.25	0.00	0.62	0.59	1.25	0.00	2.33	1.37	0.03	0.00
	GVW	4.3	3.0	4.5	24.0	16.7	28.9	0.0	68.5	40.2	73.6	0.0	366.2	63.1	8.1	0.0
N 1	Num	3	1,603	661	36	127	16	1	14	523	39	7	9	75	26	0
	Flex	0.00	0.00	0.00	0.95	0.25	0.45	2.30	0.47	1.16	0.99	1.53	0.94	1.45	0.69	0.00
	Rigid	0.00	0.00	0.00	1.08	0.26	0.70	4.37	0.53	1.86	2.01	1.49	1.03	2.10	0.88	0.00
	GVW	4.2	3.4	6.5	27.9	17.8	28.2	64.0	33.1	55.9	68.7	59.4	63.1	81.7	26.0	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9