

Monthly WIM Distribution for 01/2011

Site Names: 00096, Rigby WIM
 County: Jefferson (26)
 Funct. Class: R Principal Arterial - Other
 Location: US-20 1.4 Mi. S of US-20B

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	5	12,606	5,191	79	424	47	1	52	559	73	2	3	120	52	0
	Flex	0.00	0.00	0.00	1.13	0.24	1.01	4.13	0.58	1.87	1.78	1.47	1.01	3.14	0.32	0.00
	Rigid	0.00	0.00	0.00	1.33	0.25	1.54	8.18	0.69	3.09	3.48	1.44	1.15	4.92	0.48	0.00
	GVW	3.5	3.2	5.3	27.3	15.6	32.7	87.8	31.8	59.6	66.8	61.6	60.0	87.0	14.4	0.0
SW DIR	Num	2	6,354	2,592	37	245	21	1	27	262	36	1	2	75	23	0
	Flex	0.00	0.00	0.00	0.98	0.24	1.18	7.19	0.42	2.28	1.57	1.31	0.95	3.93	0.36	0.00
	Rigid	0.00	0.00	0.00	1.15	0.25	1.86	14.75	0.50	3.80	3.08	1.27	1.10	6.07	0.54	0.00
	GVW	3.8	3.2	5.6	26.4	15.5	34.2	130.5	30.4	64.9	61.6	77.3	57.3	94.8	15.9	0.0
NE DIR	Num	2	6,253	2,600	41	179	27	1	25	297	38	1	1	45	29	0
	Flex	0.00	0.00	0.00	1.27	0.24	0.87	5.46	0.77	1.51	1.99	2.92	1.20	1.83	0.29	0.00
	Rigid	0.00	0.00	0.00	1.50	0.25	1.27	10.71	0.90	2.46	3.88	2.89	1.35	3.02	0.45	0.00
	GVW	3.7	3.1	4.9	28.2	15.9	31.4	123.3	33.6	54.8	72.2	100.4	70.6	73.4	13.0	0.0
SW 1	Num	1	4,693	1,894	33	214	18	1	23	233	31	1	1	63	17	0
	Flex	0.00	0.00	0.00	0.94	0.23	1.21	7.32	0.42	2.32	1.56	1.45	1.04	3.96	0.35	0.00
	Rigid	0.00	0.00	0.00	1.10	0.25	1.94	15.22	0.50	3.88	3.07	1.41	1.21	6.14	0.52	0.00
	GVW	4.4	3.3	5.9	26.2	15.4	34.8	123.0	30.5	65.5	61.6	84.6	63.3	94.3	17.1	0.0
SW 2	Num	1	1,661	697	5	31	3	0	4	30	5	0	0	12	6	0
	Flex	0.00	0.00	0.00	1.37	0.26	1.08	0.00	0.38	2.02	1.72	5.54	7.78	3.82	0.59	0.00
	Rigid	0.00	0.00	0.00	1.74	0.27	1.58	0.00	0.48	3.24	3.46	5.36	8.08	5.91	0.94	0.00
	GVW	8.3	3.1	4.9	27.1	16.0	33.6	0.0	31.3	60.9	60.2	317.6	392.0	95.3	12.9	0.0
NE 2	Num	1	1,582	605	4	22	3	0	3	29	5	0	0	14	7	0
	Flex	0.00	0.00	0.00	1.03	0.22	0.60	0.00	0.78	1.29	1.22	10.88	0.00	1.63	0.15	0.00
	Rigid	0.00	0.00	0.00	1.24	0.24	0.87	0.00	0.88	2.09	2.47	10.48	0.00	2.60	0.27	0.00
	GVW	5.5	3.0	4.7	26.7	15.1	33.3	0.0	39.2	52.4	62.6	462.0	0.0	64.4	5.9	0.0
NE 1	Num	1	4,671	1,995	38	157	23	1	23	268	33	1	1	31	22	0
	Flex	0.00	0.00	0.00	1.29	0.24	0.93	5.22	0.78	1.53	2.09	3.61	1.36	1.96	0.36	0.00
	Rigid	0.00	0.00	0.00	1.53	0.26	1.35	10.35	0.92	2.50	4.07	3.58	1.53	3.30	0.57	0.00
	GVW	5.9	3.1	4.9	28.0	16.0	31.9	109.3	33.7	55.1	73.2	122.2	77.6	78.0	15.6	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9